

FENNER HTD Timing belt section 8M belt width 85



Fenner HTD drive systems conform to ISO 13050 and have a curvilinear tooth form giving more uniform distribution of shear stresses within the teeth. Tooth loads are subsequently carried by the tensile members of the belt thus providing a significant improvement over Classical Timing belts.

Characteristics

Series: HTD

Type: 8M-085

Pitch length mm	Width mm	Pitch mm	Material	Article
480	85	8	CR	480-8M85-FEN
600	85	8	CR	600-8M85-FEN
640	85	8	CR	640-8M85-FEN
720	85	8	CR	720-8M85-FEN
800	85	8	CR	800-8M85-FEN
880	85	8	CR	880-8M85-FEN
960	85	8	CR	960-8M85-FEN
1040	85	8	CR	1040-8M85-FEN
1120	85	8	CR	1120-8M85-FEN
1200	85	8	CR	1200-8M85-FEN
1280	85	8	CR	1280-8M85-FEN
1440	85	8	CR	1440-8M85-FEN
1600	85	8	CR	1600-8M85-FEN
1760	85	8	CR	1760-8M85-FEN
1800	85	8	CR	1800-8M85-FEN
2000	85	8	CR	2000-8M85-FEN
2400	85	8	CR	2400-8M85-FEN
2600	85	8	CR	2600-8M85-FEN
2800	85	8	CR	2800-8M85-FEN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.