


## FENNER Torque Drive® Plus 3 Timing belt section 14MXP belt width 170



Fenner

®

**Torque Drive PLUS 3**  
**Premium, synchronous belt**

The state of the art Fenner® Torque Drive PLUS 3 [TDP3] works with standard HTD pulleys to provide the ultimate combination of power capacity, low noise and high accuracy in a belt drive. Helically wound Glass fibre tensile members give excellent fatigue life and the low friction woven facing protects tooth surfaces from wear and aids in quiet and efficient running.

### Characteristics

**Series:** Torque Drive PLUS

**Type:** 14MXP-170

### Technical Information

- ▶ Extended temperature range -25° to +100°C.▶ Ultra compact and cost effective▶ Conditionally oil resistant

### Construction

- ▶ Enhanced compounding and glassfibre cord▶ Polyamide facing layer▶ Flexible, durable chloroprene backing polymer▶ Low friction woven nylon facing▶ Precisely formed belt teeth of medium hardness chloroprene

### Execution

- ▶ The highest power rating in the range▶ Quiet operation, even at high speeds▶ Reduced noise and extended life▶ Compact drive package▶ Runs on standard HTD pulleys

### Approval

- ▶ Static conductive in accordance with ISO 9563

| Pitch length<br>mm | Width<br>mm | Pitch<br>mm | Material | Article                |
|--------------------|-------------|-------------|----------|------------------------|
| 966                | 170         | 14          | CR       | 14MXP-966-170-GT3-FEN  |
| 1190               | 170         | 14          | CR       | 14MXP-1190-170-GT3-FEN |
| 1400               | 170         | 14          | CR       | 14MXP-1400-170-GT3-FEN |
| 1610               | 170         | 14          | CR       | 14MXP-1610-170-GT3-FEN |
| 1778               | 170         | 14          | CR       | 14MXP-1778-170-GT3-FEN |
| 1890               | 170         | 14          | CR       | 14MXP-1890-170-GT3-FEN |
| 2100               | 170         | 14          | CR       | 14MXP-2100-170-GT3-FEN |
| 2310               | 170         | 14          | CR       | 14MXP-2310-170-GT3-FEN |
| 2450               | 170         | 14          | CR       | 14MXP-2450-170-GT3-FEN |
| 2590               | 170         | 14          | CR       | 14MXP-2590-170-GT3-FEN |
| 2800               | 170         | 14          | CR       | 14MXP-2800-170-GT3-FEN |
| 3150               | 170         | 14          | CR       | 14MXP-3150-170-GT3-FEN |
| 3500               | 170         | 14          | CR       | 14MXP-3500-170-GT3-FEN |
| 3850               | 170         | 14          | CR       | 14MXP-3850-170-GT3-FEN |
| 4326               | 170         | 14          | CR       | 14MXP-4326-170-GT3-FEN |
| 4578               | 170         | 14          | CR       | 14MXP-4578-170-GT3-FEN |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.