

FENNER Torque Drive ® Plus 3 Timing belt section 8MXP belt width 30

Fenner

Torque Drive PLUS 3 Premium, synchronous belt

The state of the art Fenner® Torque Drive PLUS 3 (TDP3) works with standard HTD pulleys to provide the ultimate combination of power capacity, low noise and high accuracy in a belt drive. Helically wound Glass fibre tensile members give excellent fatigue life and the low friction woven facing protects tooth surfaces from wear and aids in quiet and efficient running.

Characteristics

Series: Torque Drive PLUS 3

Type: 8MXP-030

Technical Information

• ► Extended temperature range -25° to +100°C. ► Ultra compact and cost effective ► Conditionally oil Approval resistant

Execution

• ► The highest power rating in the range ► Quiet operation, even at high speeds▶ Reduced noise and extended life ► Compact drive package ► Runs on standard HTD pulleys

E-mail: drives.support@eriks.co.uk

▶ Static conductive in accordance with ISO 9563

Construction

• ► Enhanced compounding and glassfibre cord ► Polyamide facing layer▶ Flexible, durable chloroprene backing polymer▶ Low friction woven nylon facing ► Precisely formed belt teeth of medium hardness chloroprene

Pitch length	Width	Pitch	Material	Article
mm	mm	mm		
480	30	8	CR	8MXP-480-30-GT3-FEN
560	30	8	CR	8MXP-560-30-GT3-FEN
600	30	8	CR	8MXP-600-30-GT3-FEN
640	30	8	CR	8MXP-640-30-GT3-FEN
720	30	8	CR	8MXP-720-30-GT3-FEN
800	30	8	CR	8MXP-800-30-GT3-FEN
880	30	8	CR	8MXP-880-30-GT3-FEN
960	30	8	CR	8MXP-960-30-GT3-FEN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.



PR2277168452068017_EN_18.05.2024