



FENNER 16B-2 Taper Lock® sprocket

Fenner PLUS steel sprockets have flame hardened teeth to just below the tooth root which dramatically improves both chain and sprocket life by up to 50% and by allowing accurate mesh to be maintained longer and thereby reducing drive noise. Made for optimised performance with Fenner PLUS chain they are offered in a wide range to sizes in simplex, duplex and triplex making full use of the Taper Lock bush system for ease of mounting.

Characteristics

Series: Sprocket Fenner PLUS

Type: BS 16B-2

Pitch mm	Pitch in	Number of teeth	Taper Lock	Material	Article
25.4	1	15	2012	Steel C45 [1.0503]	1D-15T-TL-FEN
25.4	1	17	2517	Steel C45 [1.0503]	1D-17T-TL-FEN
25.4	1	19	2517	Steel C45 [1.0503]	1D-19T-TL-FEN
25.4	1	21	3020	Steel C45 [1.0503]	1D-21T-TL-FEN
25.4	1	23	3020	Steel C45 [1.0503]	1D-23T-TL-FEN
25.4	1	25	3020	Steel C45 [1.0503]	1D-25T-TL-FEN
25.4	1	30	3020	Steel C45 [1.0503]	1D-30T-TL-FEN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.