

ECON® Gearbox Series: AB Type: 4023 Cast iron IP65



Characteristics

Series: AB

Type: 4023

Housing material: Cast iron

Material quality housing: EN-JL1040

Surface protection: Polyurethane

Top flange standard: ISO 5211


Position indicator material: PP

Material worm shaft: 1.4305

Degree of protection (IP): IP65

Area of application: Inside

Suitable for underwater: No



Series	Torque [Nm]	A [mm]	B [mm]	D [mm]	d [mm]	L	M	H [mm]	h [mm]
AB 150N	150	42.5	80	ø12	ø4	See 1)	See 1)	53	26.5
AB 210N	330	52	102	ø15	ø5	See 1)	See 1)	63	28.6
AB 215N	500	52	102	ø15	ø5	See 1)	See 1)	63	28.6
AB 550N	1000	71	138	ø20	ø6	See 1)	See 1)	87	40.5
AB 880N	2000	86	200	ø20	ø6	See 1)	See 1)	94.5	42
AB 1250N	2350	104.5	220	ø20	ø6	See 1)	See 1)	103	48
AB 1950N	5500	130	285	ø25	ø8	See 1)	See 1)	124	55

1) Sizes depends of type butterfly valve and DN

Series	Shape insert	Insert dimensions mm	Mounting flange	Mounting flange 2	Mounting flange 3	Article
AB 150N	Without insert		F05	F07		EC040230000AN0N
AB 215N	Square [90°] according to ISO	22	F05	F07	F10	EC040230000CQJA
AB 215N	Without insert		F05	F07	F10	EC040230000CQ0N
AB 550N	Without insert		F10	F12		EC040230000DR0N
AB 880N	Square [90°] according to ISO	27	F16	F12		EC040230000EFLA
AB 1950N	Square [90°] according to ISO	46	F16			EC040230000GHQA

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.