

## ASCO Solenoid valve 2/2 Type: 32018 series 262-263K-LT brass cryogenic internal thread

## **Characteristics**

Series: 262-263K-LT

**Type:** 32018

Function: Normally closed (NC)

**Actuation:** Direct-acting


Electrical connection: Plug EN 175301-803 type A

Housing material: Brass Material coil housing: Epoxy Material shorting ring: Copper

Working time: 100 %

Level of protection (IP value): IP65

Explosion-proof: No SIL certified: No



Conn.	Coil type		Power	Α	В	С	D	E	F	G	н	Weight
["]				[mm]	mm	[kg]						
1/8	SPC	35030	~ 55 / 23 VA	86	50	30	48	45	68	83	100	0,7
1/8	SPC	35030	<td≥ 11,2<br="">Watt</td≥>	86	50	30	48	45	68	83	100	0,7
1/4	SPC	35031	~ 78 / 35 VA	86	50	30	48	45	68	83	100	0,7
1/4	SPC	35030	<td≥ 11,2<br="">Watt</td≥>	86	50	30	48	45	68	83	100	0,7
1/4	SPC	35030	~ 55 / 23 VA	86	50	30	48	45	68	83	100	0,7
3/8	SPC	35031	~ 78 / 35 VA	86	50	30	48	45	68	83	100	0,7
3/8	SPC	35030	<td≥ 11,2<br="">Watt</td≥>	86	50	30	48	45	68	83	100	0,7
3/8	SPC	35030	~ 55 / 23 VA	86	50	30	48	45	68	83	100	0,7

Conn.	Orifice	Coil type	dP Min.	Max. differential pressure			
				Air/gas		Cryogenic	
						liquids	
				(=DC)	(~AC)	(=DC)	[~AC]
["]	[mm]		[bar]				
1/8	3,2	SPC 35030	0	5	9	5	9
1/4	5,6	SPC 35030	0	2	-	2	-
1/4	5,6	SPC 35031	0	-	7	-	7
1/4	7,1	SPC 35030	0	1	3	1	3
3/8	5,6	SPC 35030	0	2	7	2	7

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/2

PR3368744982416871\_EN\_25.04.2024

Conn.	Orifice	Coil type	dP Min.	Max. differential pressure			
				Air/gas		Cryogenic	
						liquids	
3/8	7,1	SPC 35030	0	1	3	1	3
Medium temperature: -196° C tot 90°C							
Ambient temperature: -20° C tot 75 en50°C with coil type SPC 35031							

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice.  ${\it ERIKS shall never be liable for damage resulting from the use of the information provided.}\\$ 

E-mail: tools.support@eriks.co.uk

**ERIKS**