



ASCO Solenoid valve 2/2 Type: 32200 series 238 brass internal thread

Characteristics

Series: 238
Type: 32200
Function: Normally closed (NC)
Actuation: Indirect-acting
Electrical connection: Plug EN 175301-803 type B
Housing material: Brass
Material coil housing: Epoxy
Material shorting ring: Copper
Working time: 100 %
Level of protection (IP value): IP65
Explosion-proof: No

Application

- Water and watery neutral fluids.
- Air and neutral gases.

Technical Information

Electrical connection plug EN175301-803;

- Type A at coil powers 5 W AC; 8 W AC; 6.9 W DC; 9 W DC.
- Type B at coil power 4 W AC; 6.9 W DC.
- Conversion possible between alternating and direct voltage coil.
- **Ambient temperature:**
 - From -10 °C to 60 °C with 5W AC coil power; 8W AC; 6.9WDC; 9W DC.
 - From -10 °C to 50 °C with coil powers 4W AC and 6.9W DC.

Options

- Emergency manual operation, version MO.
- Seals and diaphragm in EPDM or FPM/FKM.
- Other supply voltages.
- Explosion-proof versions.

Size	Response time table	
	Response time opening	Response time closing
3/8"	25 ms	40 ms
1/2"	30 ms	90 ms
3/4"	55 ms	110 ms
1"	70 ms	200 ms
1.1/4"	300 ms	1000 ms
1.1/2"	300 ms	1000 ms
2"	1500 ms	2000 ms

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.