



FESTO Activated carbon filter LFX

Characteristics

Series: LFX

Ambient temperature: -10 / 60 °C

Material housing: Zinc die-casting

Manufacturer ID	Connection	Bowl guard	Maximum flow rate l/min	Ambient temperature °C	Bowl Material	Article
LFX-D-MINI		Metal	360	-10 / 60	Plastic	LFX-D-MINI
LFX-D-MIDI		Metal	900	-10 / 60	Plastic	LFX-D-MIDI
LFX-D-MAXI		Metal	1100	-10 / 60	Plastic	LFX-D-MAXI
LFX-1/2-D-MAXI	G1/2	Metal	1100	-10 / 60	Plastic	LFX-1/2-D-MAXI
LFX-1/2-D-MIDI	G1/2	Metal	900	-10 / 60	Plastic	LFX-1/2-D-MIDI
LFX-1/4-D-MIDI	G1/4	Metal	900	-10 / 60	Plastic	LFX-1/4-D-MIDI
LFX-1/4-D-MINI	G1/4	Metal	360	-10 / 60	Plastic	LFX-1/4-D-MINI
LFX-1/8-D-MINI	G1/8	Metal	360	-10 / 60	Plastic	LFX-1/8-D-MINI
LFX-3/8-D-MIDI	G3/8	Metal	900	-10 / 60	Plastic	LFX-3/8-D-MIDI

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.