



FESTO Shut-Off valve HE

Characteristics

Series: HE

Operation: Manual

Fluid: Compressed air in accordance with
ISO8573-1:2010 [7:-:-]

Flow rate at 6 Bar l/min	Port thread type	Port Size in	Port Size mm	Operating pressure bar	Function	Construction size	Housing material	Article
270			QS-6	-0.95 / 10	3/2 bistable	5	PBT-reinforced	HE-3-QS-6
278			QS-6	-0.95 / 10	2/2 bistable	5	PBT-reinforced	HE-2-QS-6
301	BSPT (R)	1/8		-0.95 / 10	3/2 bistable	5	PBT-reinforced	HE-3-1/8-QS-6
301	BSPT (R)	1/8		-0.95 / 10	3/2 bistable	5	PBT-reinforced	HE-3-1/8-1/8
307	BSPT (R)	1/8		-0.95 / 10	2/2 bistable	5	PBT-reinforced	HE-2-1/8-QS-6
380	BSPT (R)	1/4		-0.95 / 10	3/2 bistable	5	PBT-reinforced	HE-3-1/4-QS-8
380	BSPT (R)	1/4		-0.95 / 10	3/2 bistable	7	PBT-reinforced	HE-3-1/4-1/4
388			QS-8	-0.95 / 10	2/2 bistable	5	PBT-reinforced	HE-2-QS-8
390			QS-8	-0.95 / 10	3/2 bistable	5	PBT-reinforced	HE-3-QS-8
396	BSPT (R)	1/4		-0.95 / 10	2/2 bistable	5	PBT-reinforced	HE-2-1/4-QS-8
728	BSPT (R)	3/8		-0.95 / 10	2/2 bistable	7	PBT-reinforced	HE-2-3/8-QS-10
730	BSPT (R)	3/8		-0.95 / 10	3/2 bistable	7	PBT-reinforced	HE-3-3/8-3/8
733	BSPT (R)	3/8		-0.95 / 10	3/2 bistable	7	PBT-reinforced	HE-3-3/8-QS-10
761			QS-10	-0.95 / 10	2/2 bistable	7	PBT-reinforced	HE-2-QS-10
776	BSPT (R)			-0.95 / 10	2/2 bistable	7	PBT-reinforced	HE-2-1/2-QS-12
780			QS-10	-0.95 / 10	3/2 bistable	7	PBT-reinforced	HE-3-QS-10
796	BSPT (R)			-0.95 / 10	3/2 bistable	7	PBT-reinforced	HE-3-1/2-QS-12
830			QS-12	-0.95 / 10	2/2 bistable	7	PBT-reinforced	HE-2-QS-12
840			QS-12	-0.95 / 10	3/2 bistable	7	PBT-reinforced	HE-3-QS-12

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.