

FESTO Twin-Piston cylinder DPZJ



Characteristics

- Series:** DPZJ
- Function:** Double acting
- Magnetic:** Yes
- Housing material:** Aluminium alloy
- Operating temperature:** -20 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Operating pressure	Article
		mm	mm	mm	bar	
DPZJ-16-25-P-A-KF-S2	Mechanical	16	25	M 5	1 / 10	DPZJ-16-25-P-A-KF-S2
DPZJ-16-80-P-A-S2	Mechanical	16	80	M 5	1 / 10	DPZJ-16-80-P-A-S2
DPZJ-16-100-P-A-S2	Mechanical	16	100	M 5	1 / 10	DPZJ-16-100-PA-S2
DPZJ-20-25-P-A-KF-S2	Mechanical	20	25	M 5	1 / 10	DPZJ-20-25-P-A-KF-S2
DPZJ-20-25-P-A-S2	Mechanical	20	25	M 5	1 / 10	DPZJ-20-25-P-A-S2

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.