



FESTO Compact cylinder AEVULQ

Characteristics

Series: AEVULQ

Function: Single acting

Magnetic: Yes

Barrel material: Aluminium alloy

Operating temperature: -20 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure bar	Article
		mm	mm	mm	in		
AEVULQ-20-25-P-A	Mechanical	20	25	M 5		1 / 10	AEVULQ-20-25-P-A
AEVULQ-25-10-P-A	Mechanical	25	10	M 5		1 / 10	AEVULQ-25-10-P-A
AEVULQ-25-25-P-A	Mechanical	25	25	M 5		1 / 10	AEVULQ-25-25-P-A
AEVULQ-32-15-P-A	Mechanical	32	15		G1/8	0.8 / 10	AEVULQ-32-15-P-A
AEVULQ-32-15-A-P-A	Mechanical	32	15		G1/8	0.8 / 10	AEVULQ-32-15-A-P-A
AEVULQ-32-20-A-P-A	Mechanical	32	20		G1/8	0.8 / 10	AEVULQ-32-20-A-P-A
AEVULQ-63-15-P-A	Mechanical	63	15		G1/8	0.6 / 10	AEVULQ-63-15-P-A
AEVULQ-63-25-P-A	Mechanical	63	25		G1/8	0.6 / 10	AEVULQ-63-25-P-A
AEVULQ-63-25-A-P-A	Mechanical	63	25		G1/8	0.6 / 10	AEVULQ-63-25-A-P-A
AEVULQ-80-20-P-A	Mechanical	80	20		G1/8	0.6 / 10	AEVULQ-80-20-P-A

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.