



FESTO One-Way flow control valve GRLZ

Characteristics

Series: GRLZ

Execution: One-way flow control valve

Mounting: Threaded

Seal material: NBR

Operating pressure: 0.2 / 10 bar

Temperature range: -10 / 60 °C

Fluid: Compressed air in accordance with
ISO8573-1:2010 [7:4:4]

Pneumatic connection 1	Article
G1/4	GRLZ-1/4-RS-B
G1/4	GRLZ-1/4-B
G1/8	GRLZ-1/8-B
G1/8	GRLZ-1/8-RS-B
M3	GRLZ-M3
M5	GRLZ-M5-B
M5	GRLZ-M5-RS-B
PK-3	GRLZ-1/8-PK-3-B
PK-3	GRLZ-M5-PK-3-B
PK-4	GRLZ-1/8-PK-4-B
PK-4	GRLZ-M5-PK-4-B
PK-4	GRLZ-1/4-PK-4-B
PK-6	GRLZ-1/8-PK-6-B
PK-6	GRLZ-1/4-PK-6-B
QS-3	GRLZ-M5-QS-3-LF-C
QS-3	GRLZ-M3-QS-3
QS-3	GRLZ-1/8-QS-3-D
QS-3	GRLZ-M5-QS-3-D
QS-4	GRLZ-M5-QS-4-D
QS-4	GRLZ-1/8-QS4-D
QS-6	GRLZ-1/8-QS-6-D
QS-6	GRLZ-M5-QS-6-D

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.