



FESTO Pressure regulator LR

Characteristics

Series: LR

Flow rate: 8400 l/min

Flow direction: left ? right

Membrane material: NBR

Material seal: NBR

Material housing: Zinc die-cast

Temperature range [°C]: -5 / 50 °C

Pressure range bar	Operating pressure bar	Weight g	Article
0.5 / 7	1 / 10	100	LR-1/8-D-O-7-MICRO
0.5 / 12	1 / 16	300	LR-1/8-D-O-MINI
0.5 / 12	1 / 16	350	LR-1/8-D-MINI
0.5 / 12	1 / 16	300	LR-1/8-D-O-I-MINI
0.5 / 12	1 / 16	350	LR-1/8-D-I-MINI
0.5 / 7	1 / 16	300	LR-1/8-D-7O-MINI
0.5 / 7	1 / 16	300	LR-1/8-D-7O-I-MINI
0.5 / 7	1 / 16	350	LR-1/8-D-7-I-MINI
0.5 / 7	1 / 16	350	LR-1/8-D-7-MINI
0.5 / 7	1.5 / 10	150	LR-1/4-DB-7-MINI
0.5 / 7	1.5 / 10	150	LR-1/4-DB-7-O-MINI
0.5 / 12	1 / 16	350	LR-1/4-D-MINI
0.5 / 12	1 / 16	300	LR-1/4-D-O-MINI
0.5 / 12	1 / 16	350	LR-1/4-D-I-MINI
0.5 / 12	1 / 16	300	LR-1/4-D-O-I-MINI
0.5 / 7	1 / 16	350	LR-1/4-D-7-MINI
0.5 / 7	1 / 16	300	LR-1/4-D-7-O-MINI
0.5 / 7	1 / 16	300	LR-1/4-D-7-O-I-MINI
0.5 / 7	1 / 16	350	LR-1/4-D-7-I-MINI
0.5 / 12	0 / 16	720	LR-1/4-D-MIDI
0.5 / 12	0 / 16	660	LR-1/4-D-O-I-MIDI
0.5 / 12	0 / 16	660	LR-1/4-D-O-MIDI
0.5 / 12	0 / 16	720	LR-1/4-D-I-MIDI
0.5 / 7	0 / 16	660	LR-1/4-D-7-O-MIDI
0.5 / 7	0 / 16	720	LR-1/4-D-7-MIDI
0.5 / 7	0 / 16	660	LR-1/4-D-7-O-I-MIDI
0.5 / 7	0 / 16	720	LR-1/4-D-7-I-MIDI
0.5 / 12	0 / 16	660	LR-1/2-D-O-MIDI
0.5 / 12	0 / 16	720	LR-1/2-D-MIDI
0.5 / 12	0 / 16	720	LR-1/2-D-I-MIDI
0.5 / 12	0 / 16	660	LR-1/2-D-O-I-MIDI
0.5 / 7	0 / 16	720	LR-1/2-D-7-MIDI
0.5 / 7	0 / 16	660	LR-1/2-D-7O-MIDI
0.5 / 7	0 / 16	720	LR-1/2-D-7-I-MIDI
0.5 / 7	0 / 16	660	LR-1/2-D-7O-I-MIDI
0.5 / 12	1 / 16	1400	LR-1/2-D-DI-MAXI
0.5 / 7	1 / 16	1330	LR-1/2-D-7-O-DI-MAXI
0.5 / 12	0 / 16	1200	LR-1/2-D-MAXI
0.5 / 12	0 / 16	1100	LR-1/2-D-O-MAXI
0.5 / 7	0 / 16	1200	LR-1/2-D-7-MAXI

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Pressure range bar	Operating pressure bar	Weight g	Article
0.5 / 7	0 / 16	1100	LR-1/2-D-7-O-MAXI
0.5 / 12	1 / 16	300	LR-3/8-D-O-I-MINI
0.5 / 12	1 / 16	350	LR-3/8-D-MINI
0.5 / 12	1 / 16	350	LR-3/8-D-I-MINI
0.5 / 12	1 / 16	300	LR-3/8-D-O-MINI
0.5 / 7	1 / 16	300	LR-3/8-D-7-O-I-MINI
0.5 / 7	1 / 16	350	LR-3/8-D-7-I-MINI
0.5 / 7	1 / 16	350	LR-3/8-D-7-MINI
0.5 / 12	0 / 16	660	LR-3/8-D-O-I-MIDI
0.5 / 12	1 / 16	720	LR-3/8-D-MIDI
0.5 / 12	0 / 16	660	LR-3/8-D-O-MIDI
0.5 / 12	0 / 16	720	LR-3/8-D-I-MIDI
0.5 / 7	0 / 16	660	LR-3/8-D-7-O-I-MIDI
0.5 / 7	0 / 16	720	LR-3/8-D-7-MIDI
0.5 / 7	0 / 16	720	LR-3/8-D-7-I-MIDI
0.5 / 12	0 / 16	660	LR-3/4-D-O-MIDI
0.5 / 12	0 / 16	720	LR-3/4-D-MIDI
0.5 / 7	0 / 16	720	LR-3/4-D-7-MIDI
0.5 / 12	1 / 16	1330	LR-3/4-D-O-DI-MAXI
0.5 / 12	1 / 16	1400	LR-3/4-D-DI-MAXI
0.5 / 7	1 / 16	1400	LR-3/4-D-7-DI-MAXI
0.5 / 12	0 / 16	1200	LR-3/4-D-MAXI
0.5 / 12	0 / 16	1100	LR-3/4-D-O-MAXI
0.5 / 7	0 / 16	1200	LR-3/4-D-7-MAXI
0.5 / 7	0 / 16	1100	LR-3/4-D-7-O-MAXI
0.5 / 12	1 / 16	1330	LR-1-D-O-DI-MAXI
0.5 / 12	1 / 16	1400	LR-1-D-DI-MAXI
0.5 / 7	1 / 16	1400	LR-1-D-7-DI-MAXI
0.5 / 7	0 / 16	1100	LR-1-D-7-O-MAXI
0.5 / 7	1 / 10	110	LR-QS4-D-7-MICRO
0.5 / 7	1 / 10	100	LR-QS4-D-O-7-MICRO
0.5 / 7	1 / 10	100	LR-QS6-D-O-7-MICRO
0.5 / 7	1 / 10	110	LR-QS6-D-7-MICRO
0.5 / 7	1 / 10	90	LR-M5-D-7-MICRO

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.