

FESTO Pressure regulator combination LRB-K

Characteristics

Series: LRB-K

Flow rate: 3800 l/min

Flow direction: left ? right

Material seal: NBR

Material housing: Zinc die-cast

Temperature range [°C]: -5 / 50 °C



Pressure range bar	Operating pressure bar	Weight g	Article
0.5 / 12	1 / 16	1090	LRB-1/4-D-O-K3-MINI
0.5 / 12	1 / 16	1860	LRB-1/4-D-O-K5-MINI
0.5 / 12	1 / 16	760	LRB-1/4-D-O-K2-MINI
0.5 / 7	1 / 16	1480	LRB-1/4-D-7-O-K4-MINI
0.5 / 7	1 / 16	1090	LRB-1/4-D-7-O-K3-MINI
0.5 / 7	1 / 16	1860	LRB-1/4-D-7-O-K5-MINI
0.5 / 7	1 / 16	760	LRB-1/4-D-7-O-K2-MINI
0.5 / 7	1 / 16	760	LRB-3/8-D-7-O-K2-MINI
0.5 / 7	1 / 16	1090	LRB-3/8-D-7-O-K3-MINI
0.5 / 12		1950	LRB-3/8-D-O-K2-MIDI
0.5 / 12		3834	LRB-3/8-D-O-K4-MIDI
0.5 / 7	1.5 / 10	750	LRB-1/4-DB-7-O-K3-MINI
0.5 / 7	1.5 / 10	1000	LRB-1/4-DB-7-O-K4-MINI
0.5 / 12		1950	LRB-1/2-D-O-K2-MIDI
0.5 / 7		3834	LRB-1/2-D-7-O-K4-MIDI
0.5 / 7		1950	LRB-1/2-D-7-O-K2-MIDI

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.