



FESTO Double nipple NPFC-D

Characteristics

Series: NPFC-D

Ambient temperature: -20 / 150 °C

Operating pressure: -0.95 / 50 bar

Manufacturer ID	Material	Threaded connection 1	Connection 1 thread size	Threaded connection 2	Connection 2 thread size	Article
NPFC-D-2M5-M	Brass, Nickel-plated	External thread [M]	M 5	External thread [M]	M 5	NPFC-D-2M5-M
NPFC-D-2G12-M	Brass, Nickel-plated	External thread BSPP [G]	1/2	External thread BSPP [G]	1/2	NPFC-D-2G12-M
NPFC-D-G14-G12-M	Brass, Nickel-plated	External thread BSPP [G]	1/4	External thread BSPP [G]	1/2	NPFC-D-G14-G12-M
NPFC-D-2G14-M	Brass, Nickel-plated	External thread BSPP [G]	1/4	External thread BSPP [G]	1/4	NPFC-D-2G14-M
NPFC-D-G14-G38-M	Brass, Nickel-plated	External thread BSPP [G]	1/4	External thread BSPP [G]	3/8	NPFC-D-G14-G38-M
NPFC-D-G18-G14-M	Brass, Nickel-plated	External thread BSPP [G]	1/8	External thread BSPP [G]	1/4	NPFC-D-G18-G14-M
NPFC-D-2G18-M	Brass, Nickel-plated	External thread BSPP [G]	1/8	External thread BSPP [G]	1/8	NPFC-D-2G18-M
NPFC-D-G18-G38-M	Brass, Nickel-plated	External thread BSPP [G]	1/8	External thread BSPP [G]	3/8	NPFC-D-G18-G38-M
NPFC-D-G38-G12-M	Brass, Nickel-plated	External thread BSPP [G]	3/8	External thread BSPP [G]	1/2	NPFC-D-G38-G12-M
NPFC-D-2G38-M	Brass, Nickel-plated	External thread BSPP [G]	3/8	External thread BSPP [G]	3/8	NPFC-D-2G38-M
NPFC-D-2R12-M	Brass, Nickel-plated	External thread BSPT [R]	1/2	External thread BSPT [R]	1/2	NPFC-D-2R12-M
NPFC-D-R12-R34-M	Brass, Nickel-plated	External thread BSPT [R]	1/2	External thread BSPT [R]	3/4	NPFC-D-R12-R34-M
NPFC-D-R14-R12-M	Brass, Nickel-plated	External thread BSPT [R]	1/4	External thread BSPT [R]	1/2	NPFC-D-R14-R12-M
NPFC-D-2R14-M	Brass, Nickel-plated	External thread BSPT [R]	1/4	External thread BSPT [R]	1/4	NPFC-D-2R14-M
NPFC-D-R14-R38-M	Brass, Nickel-plated	External thread BSPT [R]	1/4	External thread BSPT [R]	3/8	NPFC-D-R14-R38-M
NPFC-D-R18-R14-M	Brass, Nickel-plated	External thread BSPT [R]	1/8	External thread BSPT [R]	1/4	NPFC-D-R18-R14-M
NPFC-D-2R18-M	Brass, Nickel-plated	External thread BSPT [R]	1/8	External thread BSPT [R]	1/8	NPFC-D-2R18-M
NPFC-D-R18-R38-M	Brass, Nickel-plated	External thread BSPT [R]	1/8	External thread BSPT [R]	3/8	NPFC-D-R18-R38-M
NPFC-D-2R1-M	Brass, Nickel-plated	External thread BSPT [R]	1	External thread BSPT [R]	1	NPFC-D-2R1-M
NPFC-D-2R34-M	Brass, Nickel-plated	External thread BSPT [R]	3/4	External thread BSPT [R]	3/4	NPFC-D-2R34-M
NPFC-D-R38-R12-M	Brass, Nickel-plated	External thread BSPT [R]	3/8	External thread BSPT [R]	1/2	NPFC-D-R38-R12-M
NPFC-D-2R38-M	Brass, Nickel-plated	External thread BSPT [R]	3/8	External thread BSPT [R]	3/8	NPFC-D-2R38-M

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.