



FESTO Filter MS4

Characteristics

Series: MS4

Housing material: Aluminium die-cast

Container material: Polycarbonate

Material seal: NBR

Filter element material: PE

Size	Port thread type	Port Size	Filtration level	Drain type	Flow Rate (6.3 bar - delta p = 1 bar)	Operation temperature	Operating pressure	Weight	Article
		in	µm		NI/min	°C	bar	g	
4	Parallel (G)	1/8	5	Automatic	1000	5 / 60	2 / 12	189	MS4-LF-1/8-CRV
4	Parallel (G)	1/8	40	Manual	1100	-10 / 60	0 / 14	189	MS4-LF-1/8-ERM
4	Parallel (G)	1/8	5	Manual	1000	-10 / 60	0 / 14	189	MS4-LF-1/8-CRM
4	Parallel (G)	1/4	40	Automatic	1700	5 / 60	2 / 12	349	MS4-LF-1/4-EUV
4	Parallel (G)	1/4	40	Automatic	1700	5 / 60	2 / 12	189	MS4-LF-1/4-ERV
4	Parallel (G)	1/4	5	Automatic	1300	5 / 60	2 / 12	189	MS4-LF-1/4-CRV
4	Parallel (G)	1/4	40	Manual	1700	-10 / 60	0 / 14	189	MS4-LF-1/4-ERM-Z
4	Parallel (G)	1/4	5	Manual	1300	-10 / 60	0 / 14	189	MS4-LF-1/4-CRM
4	Parallel (G)	1/4	5	Manual	1300	-10 / 60	0 / 14	349	MS4-LF-1/4-CUM
4	Parallel (G)	1/4	40	Manual	1700	-10 / 60	0 / 14	189	MS4-LF-1/4-ERM
4	Parallel (G)	1/4	40	Manual	1700	-10 / 60	0 / 14	349	MS4-LF-1/4-EUM

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.