



FESTO Filter MS6

Characteristics

Series: MS6

Housing material: Aluminium die-cast

Container material: Polycarbonate

Material seal: NBR

Filter element material: PE

Size	Port thread type	Port Size	Filtration level	Drain type	Flow Rate (6.3 bar - delta p = 1 bar)	Operation temperature	Operating pressure	Weight	Article
		in	µm		NI/min	°C	bar	g	
6	Parallel (G)	1/4	5	Automatic	2000	5 / 60	2 / 12	600	MS6-LF-1/4-CRV
6	Parallel (G)	1/4	5	Manual	2000	-10 / 60	0 / 20	600	MS6-LF-1/4-CRM
6	Parallel (G)	1/4	40	Manual	2500	-10 / 60	0 / 20	600	MS6-LF-1/4-ERM
6	Parallel (G)	3/8	5	Automatic	3000	5 / 60	2 / 12	600	MS6-LF-3/8-CRV
6	Parallel (G)	3/8	5	Manual	3000	-10 / 60	0 / 20	600	MS6-LF-3/8-CRM
6	Parallel (G)	1/2	40	Automatic	4100	5 / 60	2 / 12	600	MS6-LF-1/2-ERV-Z
6	Parallel (G)	1/2	5	Automatic	3200	5 / 60	2 / 12	600	MS6-LF-1/2-CRV-Z
6	Parallel (G)	1/2	5	Automatic	3200	5 / 60	2 / 12	600	MS6-LF-1/2-CRV
6	Parallel (G)	1/2	5	Automatic	3200	5 / 60	2 / 12	820	MS6-LF-1/2-CUV
6	Parallel (G)	1/2	40	Automatic	4100	5 / 60	2 / 12	600	MS6-LF-1/2-ERV
6	Parallel (G)	1/2	40	Automatic	4100	5 / 60	2 / 12	820	MS6-LF-1/2-EUV
6	Parallel (G)	1/2	40	Manual	4100	-10 / 60	0 / 20	600	MS6-LF-1/2-ERM-Z
6	Parallel (G)	1/2	40	Manual	4100	-10 / 60	0 / 20	820	MS6-LF-1/2-EUM
6	Parallel (G)	1/2	40	Manual	4100	-10 / 60	0 / 20	600	MS6-LF-1/2-ERM
6	Parallel (G)	1/2	5	Manual	3200	-10 / 60	0 / 20	820	MS6-LF-1/2-CUM

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.