



FESTO Rotary indexing table DHTG

Characteristics

Series: DHTG

Operation: Double acting

Cushioning: Shock absorber, adjustable

Housing material: Aluminium alloy

Fluid: Compressed air in accordance with
ISO8573-1:2010 [7:4:4]

Ambient temperature: 5 / 60 °C

Operating pressure: 4 / 8 bar

Sound pressure level: < = 70 dB(A)

Manufacturer ID	Construction size	Pitch	Port Size	Theoretical torque at 6 bar		Article
				in	Nm	
DHTG-65-2-A	65	2	M5		2.1	DHTG-65-2-A
DHTG-65-3-A	65	3	M5		2.1	DHTG-65-3-A
DHTG-65-4-A	65	4	M5		2.1	DHTG-65-4-A
DHTG-65-8-A	65	8	M5		2.1	DHTG-65-8-A
DHTG-65-12-A	65	12	M5		2.1	DHTG-65-12-A
DHTG-65-24-A	65	24	M5		2.1	DHTG-65-24-A
DHTG-90-2-A	90	2	M5		4.4	DHTG-90-2-A
DHTG-90-3-A	90	3	M5		4.4	DHTG-90-3-A
DHTG-90-4-A	90	4	M5		4.4	DHTG-90-4-A
DHTG-90-6-A	90	6	M5		4.4	DHTG-90-6-A
DHTG-90-8-A	90	8	M5		4.4	DHTG-90-8-A
DHTG-90-12-A	90	12	M5		4.4	DHTG-90-12-A
DHTG-90-24-A	90	24	M5		4.4	DHTG-90-24-A
DHTG-140-3-A	140	3	1/8		18.1	DHTG-140-3-A
DHTG-140-4-A	140	4	1/8		18.1	DHTG-140-4-A
DHTG-140-6-A	140	6	1/8		18.1	DHTG-140-6-A
DHTG-140-24-A	140	24	1/8		18.1	DHTG-140-24-A
DHTG-220-3-A	220	3	1/8		58.9	DHTG-220-3-A
DHTG-220-4-A	220	4	1/8		58.9	DHTG-220-4-A
DHTG-220-6-A	220	6	1/8		58.9	DHTG-220-6-A
DHTG-220-12-A	220	12	1/8		58.9	DHTG-220-12-A

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.