



FESTO Soft-start valve MS-DE

Characteristics

Series: MS-DE

Housing material: Aluminium die-cast

Seal material: NBR

Operating pressure: 4 / 10 bar

Manufacturer ID	Type of actuation	Connection	Port Size in	With pressure gauge	With pressure sensor	With silencer	With console	Flow direction	Nominal flow rate l/min	Article
MS6-DE-1/4-10V24	Electrical	BSPP(G)	1/4	No	No	No	No	left ? right		MS6-DE-1/4-10V24
MS4-DE-1/4-10V24	Electrical	BSPP(G)	1/4	No	No	No	No	left ? right	2000	MS4-DE-1/4-10V24
MS6-DE-3/8-10V24	Electrical	BSPP(G)	3/8	No	No	No	No	left ? right		MS6-DE-3/8-10V24
MS6-DE-1/2-10V24	Electrical	NPT	1/2-14	No	No	No	No	left ? right	6450	MS6-DE-1/2-10V24

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.