



FESTO Soft-start valve MS-DL

Characteristics

Series: MS-DL

Housing material: Aluminium die-cast

Seal material: NBR

With console: No

Manufacturer ID	Type of actuation	Connection	Port Size	With pressure gauge	With pressure sensor	With silencer	Flow direction	Nominal flow rate	Operating pressure	Article
			in					l/min		
MS12-DL-G	Pneumatic			No	No	No	non reversible	25000 .. 42000	2 / 20	MS12-DL-G
MS4-DL-1/8	Pneumatic	BSPP[G]	1/8	No	No	No	left ? right	1000	4 / 14	MS4-DL-1/8
MS6-DL-1/4	Pneumatic	BSPP[G]	1/4	No	No	No	left ? right		4 / 18	MS6-DL-1/4
MS4-DL-1/4	Pneumatic	BSPP[G]	1/4	No	No	No	left ? right	2000	4 / 14	MS4-DL-1/4
MS4-DL-1/4-Z	Pneumatic	BSPP[G]	1/4	No	No	No	right ? left	2000	4 / 14	MS4-DL-1/4-Z
MS6-DL-3/8	Pneumatic	BSPP[G]	3/8	No	No	No	left ? right		4 / 18	MS6-DL-3/8
MS6-DL-1/2	Pneumatic	BSPP[G]	1/2	No	No	No	left ? right	6450	4 / 18	MS6-DL-1/2
MS6-DL-1/2-Z	Pneumatic	BSPP[G]	1/2	No	No	No	right ? left	6450	4 / 18	MS6-DL-1/2-Z

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.