FESTO Cartridge cylinder EGZ



Characteristics

Series: EGZ

Function: Single acting

Housing material: Brass, Nickel-plated Operating temperature: -20 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Operating pressure	Article
		mm	mm	mm	bar	
EGZ-6-5	Without	6	5	M 3	2/8	EGZ-6-5
EGZ-6-10	Without	6	10	M 3	2/8	EGZ-6-10
EGZ-6-15	Without	6	15	M 3	2/8	EGZ-6-15
EGZ-10-5	Without	10	5	M 5	2/8	EGZ-10-5
EGZ-10-10	Without	10	10	M 5	2/8	EGZ-10-10
EGZ-16-5	Without	16	5	M 5	2/8	EGZ-16-5
EGZ-16-10	Without	16	10	M 5	2/8	EGZ-16-10
EGZ-16-15	Without	16	15	M 5	2/8	EGZ-16-15

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR455266037360768_EN_19.05.2024