



FESTO Clamping module EV

Characteristics

- Series:** EV
- Function:** Single acting
- Housing material:** Aluminium die-cast
- Operating temperature:** -10 / 40 °C

Manufacturer ID	Stroke length mm	Port Size mm	Article
EV-12-3	3	M 3	EV-12-3
EV-10/30-3	3	M 3	EV-10/30-3
EV-25-4	4	M 3	EV-25-4
EV-16-4	4	M 3	EV-16-4
EV-20-4	4	M 3	EV-20-4
EV-15/40-4	4	M 5	EV-15/40-4
EV-15/63-4	4	M 5	EV-15/63-4
EV-40-5	5	M 3	EV-40-5
EV-32-5	5	M 3	EV-32-5
EV-63-5	5	M 3	EV-63-5
EV-50-5	5	M 3	EV-50-5
EV-20/120-5	5	M 5	EV-20/120-5
EV-20/180-5	5	M 5	EV-20/180-5
EV-20/75-5	5	M 5	EV-20/75-5

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.