

FESTO Plastic tubing PLN

Characteristics

Series: PLN

Hose material: Polyethylene



Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure at 20 °C	Roller length	Colour	Minimum bending radius	FDA quality mark	Hardness	Weight per meter	Article
mm	mm	mm	bar	m		mm			g	
2.9	0.75	4	14	50	Black	12	Yes	0	5.6	PLN-4X0.75-BLACK
2.9	0.75	4	14	50	Natural	12	Yes	0	5.6	PLN-4X0.75-NATURAL
4	1	6	14	50	Blue	11	Yes	0	14.7	PLN-6X1-BL
4	1	6	14	50	Natural	11	Yes	0	14.7	PLN-6X1-NATURAL
4	1	6	14	50	Red	11	Yes	0	14.7	PLN-6X1-RT
4	1	6	14	50	Silver	11	Yes	0	14.7	PLN-6X1-SI
5.9	1.25	8	14	50	Black	23	Yes	0	21.4	PLN-8X1.25-BLACK
5.9	1.25	8	14	50	Blue	23	Yes	0	21.4	PLN-8X1.25-BL
5.9	1.25	8	14	50	Red	23	Yes	0	21.4	PLN-8X1.25-RT
7	1.5	10	14	50	Black	22	Yes	0	37.5	PLN-10X1.5-BLACK
8.4	1.75	12	14	50	Black	23	Yes	0	54	PLN-12X1.75-BLACK
10	2	14	14	50	Natural	40	Yes	0	70	PLN-14X2-NT
12	2	16	14	50	Black	55	Yes	0	82	PLN-16X2-BLACK
12	2	16	14	50	Blue	55	Yes	0	82	PLN-16X2-BL
12	2	16	14	50	Natural	55	Yes	0	82	PLN-16X2-NATURAL
12	2	16	14	50	Red	55	Yes	0	82	PLN-16X2-RT
12	2	16	14	50	Silver	55	Yes	0	82	PLN-16X2-SI

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.