

FESTO Plastic tubing PUN-H

Characteristics

Series: PUN-H

Hose material: TPE-U(PU)



Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure at 20 °C	Roller length	Colour	Minimum bending radius	FDA quality mark	Hardness	Weight per meter	Article
mm	mm	mm	bar	m		mm			g	
1.2	0.4	2	10	50	Black	5	Yes	D 52 +/-3	2.4	PUN-H-2X0.4-SW
2.1	0.5	3	10	50	Black	6	Yes	D 52 +/-3	4.2	PUN-H-3X0.5-BLACK
2.1	0.5	3	10	50	Blue	6	Yes	D 52 +/-3	4.2	PUN-H-3X0.5-BLUE
2.1	0.5	3	10	50	Green	6	Yes	D 52 +/-3	4.2	PUN-H-3X0.5-GN
2.1	0.5	3	10	50	Natural	6	Yes	D 52 +/-3	4.2	PUN-H-3X0.5-CLEAR
2.1	0.5	3	10	50	Silver	6	Yes	D 52 +/-3	4.2	PUN-H-3X0.5-SI
2.1	0.5	3	10	50	Yellow	6	Yes	D 52 +/-3	4.2	PUN-H-3X0.5-GE
2.6	0.75	4	10	500	Black	8	Yes	D 52 +/-3	8.5	PUN-H-4X0.75-SW-500
2.6	0.75	4	10	50	Blue	8	Yes	D 52 +/-3	8.5	PUN-H-4X0.75-BLUE
2.6	0.75	4	10	50	Green	8	Yes	D 52 +/-3	8.5	PUN-H-4X0.75-GN
2.6	0.75	4	10	50	Natural	8	Yes	D 52 +/-3	8.5	PUN-H-4X0.75-CLEAR
2.6	0.75	4	10	50	Red	8	Yes	D 52 +/-3	8.5	PUN-H-4X0.75-RT
2.6	0.75	4	10	50	Silver	8	Yes	D 52 +/-3	8.5	PUN-H-4X0.75-SI
2.6	0.75	4	10	50	Transparent blue	8	Yes	D 52 +/-3	8.5	PUN-H-4X0.75-TBL
2.6	0.75	4	10	50	Yellow	8	Yes	D 52 +/-3	8.5	PUN-H-4X0.75-GE
4	1	6	10	50	Black	10	Yes	D 52 +/-3	18.3	PUN-H-6X1-SW
4	1	6	10	500	Black	10	Yes	D 52 +/-3	18.3	PUN-H-6X1-SW-500
4	1	6	10	500	Blue	10	Yes	D 52 +/-3	18.3	PUN-H-6X1-BL-500
4	1	6	10	50	Blue	10	Yes	D 52 +/-3	18.3	PUN-H-6X1-BLUE
4	1	6	10	50	Green	10	Yes	D 52 +/-3	18.3	PUN-H-6X1-GN
4	1	6	10	50	Natural	10	Yes	D 52 +/-3	18.3	PUN-H-6X1-NT
4	1	6	10	500	Natural	10	Yes	D 52 +/-3	18.3	PUN-H-6X1-NT-500
4	1	6	10	50	Red	10	Yes	D 52 +/-3	18.3	PUN-H-6X1-RT
4	1	6	10	50	Silver	10	Yes	D 52 +/-3	18.3	PUN-H-6X1-SI
4	1	6	10	500	Silver	10	Yes	D 52 +/-3	18.3	PUN-H-6X1-SI-500
4	1	6	10	50	Yellow	10	Yes	D 52 +/-3	18.3	PUN-H-6X1-GE
5.7	1.25	8	10	50	Black	21	Yes	D 52 +/-3	28.7	PUN-H-8X1.25-BLACK

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure at 20 °C	Roller length	Colour	Minimum bending radius	FDA quality mark	Hardness	Weight per meter	Article
mm	mm	mm	bar	m		mm			g	
5.7	1.25	8	10	400	Black	21	Yes	D 52 +/-3	28.7	PUN-H-8X1.25-SW-400
5.7	1.25	8	10	50	Blue	21	Yes	D 52 +/-3	28.7	PUN-H-8X1.25-BLUE
5.7	1.25	8	10	50	Green	21	Yes	D 52 +/-3	28.7	PUN-H-8X1.25-GN
5.7	1.25	8	10	50	Red	21	Yes	D 52 +/-3	28.7	PUN-H-8X1.25-RT
5.7	1.25	8	10	50	Silver	21	Yes	D 52 +/-3	28.7	PUN-H-8X1.25-SI
5.7	1.25	8	10	50	Yellow	21	Yes	D 52 +/-3	28.7	PUN-H-8X1.25-GE
7	1.5	10	10	50	Black	28	Yes	D 52 +/-3	46.5	PUN-H-10X1.5-BLACK
7	1.5	10	10	50	Blue	28	Yes	D 52 +/-3	46.5	PUN-H-10X1.5-BLUE
7	1.5	10	10	50	Green	28	Yes	D 52 +/-3	46.5	PUN-H-10X1.5-GN
7	1.5	10	10	50	Red	28	Yes	D 52 +/-3	46.5	PUN-H-10X1.5-RT
7	1.5	10	10	50	Silver	28	Yes	D 52 +/-3	46.5	PUN-H-10X1.5-SI
7	1.5	10	10	50	Transparent blue	28	Yes	D 52 +/-3	46.5	PUN-H-10X1.5-TBL
7	1.5	10	10	50	Yellow	28	Yes	D 52 +/-3	46.5	PUN-H-10X1.5-GE
8	2	12	10	200	Black	33	Yes	D 52 +/-3	72.9	PUN-H-12X2-SW-200
8	2	12	10	50	Blue	33	Yes	D 52 +/-3	72.9	PUN-H-12X2-BLUE
8	2	12	10	200	Blue	33	Yes	D 52 +/-3	72.9	PUN-H-12X2-BL-200
8	2	12	10	50	Green	33	Yes	D 52 +/-3	72.9	PUN-H-12X2-GN
8	2	12	10	50	Red	33	Yes	D 52 +/-3	72.9	PUN-H-12X2-RT
8	2	12	10	50	Silver	33	Yes	D 52 +/-3	72.9	PUN-H-12X2-SI
8	2	12	10	200	Silver	33	Yes	D 52 +/-3	72.9	PUN-H-12X2-SI-200
8	2	12	10	50	Yellow	33	Yes	D 52 +/-3	72.9	PUN-H-12X2-GE
9.8	2	14	10	50	Black	38	Yes	D 52 +/-3	91	PUN-H-14X2-SW
9.8	2	14	10	50	Blue	38	Yes	D 52 +/-3	91	PUN-H-14X2-BL
9.8	2	14	10	50	Natural	38	Yes	D 52 +/-3	91	PUN-H-14X2-NT
11	2.5	16	10	50	Black	38	Yes	D 52 +/-3	123	PUN-H-16X2.5-BLACK
11	2.5	16	10		Blue	38	Yes	D 52 +/-3	123	PUN-H-16X2.5-BLUE
11	2.5	16	10	50	Green	38	Yes	D 52 +/-3	123	PUN-H-16X2.5-GN
11	2.5	16	10	50	Red	38	Yes	D 52 +/-3	123	PUN-H-16X2.5-RT
11	2.5	16	10	50	Silver	38	Yes	D 52 +/-3	123	PUN-H-16X2.5-SI
11	2.5	16	10	50	Yellow	38	Yes	D 52 +/-3	123	PUN-H-16X2.5-GE

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.