

FESTO Plastic tubing flame retardant PAN-V0

Characteristics

Series: PAN-V0

Hose material: PVC-P/PA12-P

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure at 20 °C	Roller length	Colour	Minimum bending radius	Hardness	Weight per meter	Article
mm	mm	mm	bar	m		mm		g	
4	1	8	12	50	Black	13	A 57 +/-3 / D 57 +/-3	49	PAN-V0-6X1-BLACK
4	1	8	12	20	Green	13	A 57 +/-3 / D 57 +/-3	49	PAN-V0-6X1-GREEN
4	1	8	12	20	Red	13	A 57 +/-3 / D 57 +/-3	49	PAN-V0-6X1-RED
4	1	8	12	20	White	13	A 57 +/-3 / D 57 +/-3	49	PAN-V0-6X1-WHITE
4	1	8	12	20	Yellow	13	A 57 +/-3 / D 57 +/-3	49	PAN-V0-6X1-YELLOW
6	1	10	12	50	Black	24	A 57 +/-3 / D 57 +/-3	65	PAN-V0-8X1-BLACK
6	1	10	12	20	Green	24	A 57 +/-3 / D 57 +/-3	65	PAN-V0-8X1-GREEN
6	1	10	12	20	Red	24	A 57 +/-3 / D 57 +/-3	65	PAN-V0-8X1-RED
6	1	10	12	20	White	24	A 57 +/-3 / D 57 +/-3	65	PAN-V0-8X1-WHITE
6	1	10	12	20	Yellow	24	A 57 +/-3 / D 57 +/-3	65	PAN-V0-8X1-YELLOW
7.5	1.25	12	12	50	Black	34	A 57 +/-3 / D 57 +/-3	88	PAN-V0-10X1.25-BLACK
7.5	1.25	12	12	20	Green	34	A 57 +/-3 / D 57 +/-3	88	PAN-V0-10X1.25-GREEN
7.5	1.25	12	12	20	Red	34	A 57 +/-3 / D 57 +/-3	88	PAN-V0-10X1.25-RED
7.5	1.25	12	12	20	White	34	A 57 +/-3 / D 57 +/-3	88	PAN-V0-10X1.25-WHITE
7.5	1.25	12	12	20	Yellow	34	A 57 +/-3 / D 57 +/-3	88	PAN-V0-10X1.25-YELLOW
9	1.5	14	12	50	Black	43	A 57 +/-3 / D 57 +/-3	133	PAN-V0-12X1.5-BLACK
9	1.5	14	12	20	Blue	43	A 57 +/-3 / D 57 +/-3	133	PAN-V0-12X1.5-BLUE
9	1.5	14	12	20	Green	43	A 57 +/-3 / D 57 +/-3	133	PAN-V0-12X1.5-GREEN
9	1.5	14	12	20	Red	43	A 57 +/-3 / D 57 +/-3	133	PAN-V0-12X1.5-RED
9	1.5	14	12	20	White	43	A 57 +/-3 / D 57 +/-3	133	PAN-V0-12X1.5-WHITE
9	1.5	14	12	20	Yellow	43	A 57 +/-3 / D 57 +/-3	133	PAN-V0-12X1.5-YELLOW

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.