

FESTO Plastic tubing flame retardant PUN-V0



Characteristics

Series: PUN-V0

Hose material: TPE-U(PU)

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure at 20 °C	Roller length	Colour	Minimum bending radius	Hardness	Weight per meter	Article
mm	mm	mm	bar	m		mm		g	
2	1	4	10	50	Black	10	D 54 +/-3	12	PUN-V0-4X1-SW-C
2	1	4	10	50	Blue	10	D 54 +/-3	12	PUN-V0-4X1-BL-C
2	2	6	30	50	Black	7	D 54 +/-3	32	PUN-V0-6X2-SW-C
2	2	6	30	50	Blue	7	D 54 +/-3	32	PUN-V0-6X2-BL-C
2	2	6	30	50	White	7	D 54 +/-3	32	PUN-V0-6X2-W-S-C
4	1	6	10	50	Black	12	D 54 +/-3	20	PUN-V0-6X1-BLACK
4	1	6	10	50	Blue	12	D 54 +/-3	20	PUN-V0-6X1-BLUE
4	1	6	10	50	Brown	12	D 54 +/-3	20	PUN-V0-6X1-BROWN
4	1	6	10	50	Red	12	D 54 +/-3	20	PUN-V0-6X1-RED
4	1	6	10	50	White	12	D 54 +/-3	20	PUN-V0-6X1-WHITE
4	1	6	10	50	Yellow	12	D 54 +/-3	20	PUN-V0-6X1-YELLOW
4	2	8	20	50	Black	9	D 54 +/-3	49	PUN-V0-8X2-SW-C
4	2	8	20	50	Blue	9	D 54 +/-3	49	PUN-V0-8X2-BL-C
5.7	1.25	8	10	50	Black	18	D 54 +/-3	31	PUN-V0-8X1.25-BLACK
5.7	1.25	8	10	50	Brown	18	D 54 +/-3	31	PUN-V0-8X1.25-BROWN
5.7	1.25	8	10	50	Green	18	D 54 +/-3	31	PUN-V0-8X1.25-GREEN
5.7	1.25	8	10	50	Red	18	D 54 +/-3	31	PUN-V0-8X1.25-RED
5.7	1.25	8	10	50	White	18	D 54 +/-3	31	PUN-V0-8X1.25-WHITE
5.7	1.25	8	10	50	Yellow	18	D 54 +/-3	31	PUN-V0-8X1.25-YELLOW
6	2	10	16	50	Black	12	D 54 +/-3	64	PUN-V0-10X2-SW-C
6	2	10	16	50	Blue	12	D 54 +/-3	64	PUN-V0-10X2-BL-C
7	1.5	10	10	50	Black	20	D 54 +/-3	51	PUN-V0-10X1.5-BLACK
7	1.5	10	10	50	Blue	20	D 54 +/-3	51	PUN-V0-10X1.5-BLUE
7	1.5	10	10	50	Brown	20	D 54 +/-3	51	PUN-V0-10X1.5-BROWN
7	1.5	10	10	50	Green	20	D 54 +/-3	51	PUN-V0-10X1.5-GREEN
7	1.5	10	10	50	Red	20	D 54 +/-3	51	PUN-V0-10X1.5-RED
7	1.5	10	10	50	White	20	D 54 +/-3	51	PUN-V0-10X1.5-WHITE

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure at 20 °C	Roller length	Colour	Minimum bending radius	Hardness	Weight per meter	Article
mm	mm	mm	bar	m		mm		g	
7	1.5	10	10	50	Yellow	20	D 54 +/-3	51	PUN-V0-10X1.5-YELLOW
8	2	12	10	50	Black	19	D 54 +/-3	80	PUN-V0-12X2-SW-C
8	2	12	10	50	Yellow	19	D 54 +/-3	80	PUN-V0-12X2-GE-C

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.