



FESTO Swivel/Linear unit DSL

Characteristics

- Series:** DSL
- Function:** Double acting
- Housing material:** Anodised aluminium
- Operating temperature:** -10 / 60 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure bar	Article
		mm	mm	mm	in		
DSL-16-80-270-CC-A-S20-B	Mechanical	16	80	M 5		2.5 / 8	DSL-16-80-270-CC-A-S20-B
DSL-20-100-270-CC-A-S2-B	Mechanical	20	100	M 5		2.5 / 8	DSL-20-100-270-CC-A-S2-B
DSL-32-25-270-CC-A-S20-B	Mechanical	32	25		G1/8	2.5 / 8	DSL-32-25-270-CC-A-S20-B
DSL-40-125-270-CC-A-S2-B	Mechanical	40	125		G1/8	2.5 / 8	DSL-40-125-270-CC-A-S2-B
DSL-40-160-270-P-A-S20-B	Mechanical	40	160		G1/8	2.5 / 8	DSL-40-160-270-P-A-S20-B

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.