



FESTO Linear/Swivel clamp CLR

Characteristics

- Series:** CLR
- Function:** Double acting
- Housing material:** Anodised aluminium
- Operating temperature:** -10 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure	Article
		mm	mm	mm	in		
CLR-12-10-R-P-A	Mechanical	12	10	M 5		2 / 10	CLR-12-10-R-P-A
CLR-12-10-L-P-A	Mechanical	12	10	M 5		2 / 10	CLR-12-10-L-P-A
CLR-20-10-R-P-A	Mechanical	20	10	M 5		2 / 10	CLR-20-10-R-P-A
CLR-20-10-L-P-A	Mechanical	20	10	M 5		2 / 10	CLR-20-10-L-P-A
CLR-20-20-R-P-A	Mechanical	20	20	M 5		2 / 10	CLR-20-20-R-P-A
CLR-20-20-L-P-A	Mechanical	20	20	M 5		2 / 10	CLR-20-20-L-P-A
CLR-25-10-R-P-A	Mechanical	25	10	M 5		2 / 10	CLR-25-10-R-P-A
CLR-25-10-L-P-A	Mechanical	25	10	M 5		2 / 10	CLR-25-10-L-P-A
CLR-25-20-L-P-A	Mechanical	25	20	M 5		2 / 10	CLR-25-20-L-P-A
CLR-32-10-R-P-A-B	Mechanical	32	10		G1/8	2 / 10	CLR-32-10-R-P-A-B
CLR-32-20-R-P-A-B	Mechanical	32	20		G1/8	2 / 10	CLR-32-20-R-P-A-B
CLR-50-50-R-P-A	Mechanical	50	50		G1/8	2 / 10	CLR-50-50-R-P-A
CLR-50-50-L-P-A	Mechanical	50	50		G1/8	2 / 10	CLR-50-50-L-P-A

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.