FESTO Barbed L-Fitting LCN



Characteristics

Series: LCN

Operating temperature: $0 / 60 \, ^{\circ}\text{C}$ Operating pressure: -0.95 / 10 bar

Manufacturer ID	Material	Connection 1	Connection 2	Nominal size mm	Wrench width mm	Article
LCN-M5-PK-2	Zinc die-cast / Aluminium	Tubing O.D. 3mm	M5	7	7	LCN-M5-PK-2
LCN-1/8-PK-3	Zinc die-cast / Aluminium	Tubing O.D. 4mm	1/8" BSPP(G)	13	13	LCN-1/8-PK-3
LCN-1/4-PK-4	Zinc die-cast / Aluminium	Tubing O.D. 6mm	1/4" BSPP(G)	17	17	LCN-1/4-PK-4
LCN-1/8-PK-4	Zinc die-cast / Aluminium	Tubing O.D. 6mm	1/8" BSPP(G)	13	13	LCN-1/8-PK-4
LCN-1/4-PK-6	Zinc die-cast / Aluminium	Tubing O.D. 8mm	1/4" BSPP(G)	17	17	LCN-1/4-PK-6
LCN-1/8-PK-6	Zinc die-cast / Aluminium	Tubing O.D. 8mm	1/8" BSPP(G)	13	13	LCN-1/8-PK-6

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR455266037360950_EN_04.05.2024