



FESTO Elbow quick connector LCK

Characteristics

Series: LCK
Operating temperature: -10 / 60 °C
Operating pressure: 0 / 16 bar

Manufacturer ID	Material	Connection 1 mm	Connection 2 mm	Nominal size mm	Wrench width mm	Wrench width 2 mm	Article
LCK-1/4-PK-4	Zinc die-cast	CK connection 4mm	1/4" BSPP(G)	17	17	12	LCK-1/4-PK4-AL
LCK-1/8-PK-4	Zinc die-cast	CK connection 4mm	1/8" BSPP(G)	13	13	12	LCK-1/8-PK4-AL
LCK-1/8-PK-6	Zinc die-cast	CK connection 6mm	1/8" BSPP(G)	13	13	14	LCK-1/8-PK6-AL
LCK-1/4-PK-9	Zinc die-cast	CK connection 9mm	1/4" BSPP(G)	17	17	19	LCK-1/4-PK-9
LCK-1/4-PK-4-KU	POM	CK connection 4mm	1/4" BSPP(G)	17	17	12	LCK-1/4-PK4-KU
LCK-1/4-PK-6-KU	POM	CK connection 6mm	1/4" BSPP(G)	17	17	14	LCK-1/4-PK6-KU
LCK-1/8-PK-6-KU	POM	CK connection 6mm	1/8" BSPP(G)	13	13	14	LCK-1/8-PK-6-KU

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.