



FESTO Mini slide EGSL

Characteristics

Series: EGSL

Operating temperature: 0 / 60 °C

Degree of protection (IP): 40

Spindle type	Construction size	Stroke length	Spindle pitch	Repetition accuracy	Max. feed force Fx	Article
		mm	mm/U	mm	N	
Ball screw	35	50	8	±0.015	75	EGSL-BS-35-50-8P
Ball screw	45	100	3	±0.015	150	EGSL-BS-45-100-3P
Ball screw	45	200	3	±0.015	150	EGSL-BS-45-200-3P
Ball screw	45	200	10	±0.015	150	EGSL-BS-45-200-10P
Ball screw	55	100	5	±0.015	300	EGSL-BS-55-100-5P
Ball screw	55	100	12.7	±0.015	300	EGSL-BS-55-100-12.7P
Ball screw	55	200	5	±0.015	300	EGSL-BS-55-200-5P
Ball screw	55	200	12.7	±0.015	300	EGSL-BS-55-200-12.7P
Ball screw	55	250	5	±0.015	300	EGSL-BS-55-250-5P
Ball screw	55	250	12.7	±0.015	300	EGSL-BS-55-250-12.7P
Ball screw	75	100	10	±0.015	450	EGSL-BS-75-100-10P
Ball screw	75	100	20	±0.015	450	EGSL-BS-75-100-20P
Ball screw	75	200	20	±0.015	450	EGSL-BS-75-200-20P
Ball screw	75	300	10	±0.015	450	EGSL-BS-75-300-10P
Ball screw	75	300	20	±0.015	450	EGSL-BS-75-300-20P

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.