

FESTO Proximity sensor SIEF



Characteristics

Series: SIEF

Standard: EN 60947-5-2

Degree of protection (IP): IP68

Manufacturer ID	Size	Voltage	Max. switching current	Max. voltage drop V	Cable length mm	Electrical connection	Temperature range °C	Switching distance mm	Article
SIEF-M8B-NS-K-L	M 12	10 - 30 V DC	150		2500	Cable, 3-core	-30 / 70	1.5	SIEF-M8B-NS-K-L
SIEF-M12B-NS-K-L	M 12	10 - 30 V DC	200		2500	Cable, 3-core	-30 / 70	3	SIEF-M12B-NS-K-L
SIEF-M8B-PS-S-L	M 12	10 - 30 V DC	150			Plug, M8x1, 3-pin	-30 / 85	1.5	SIEF-M8B-PS-S-L
SIEF-M8B-NS-S-L	M 12	10 - 30 V DC	150			Plug, M8x1, 3-pin	-30 / 85	1.5	SIEF-M8B-NS-S-L
SIEF-M12B-PS-S-L	M 12	10 - 30 V DC	200			Plug, M12x1, 3-pin	-30 / 85	3	SIEF-M12B-PS-S-L
SIEF-M12B-NS-S-L	M 12	10 - 30 V DC	200			Plug, M12x1, 3-pin	-30 / 85	3	SIEF-M12B-NS-S-L
SIEF-M12B-PS-S-L-WA	M 12	10 - 30 V DC	200	1.8		Plug, M12x1, 3-pin	-30 / 85	3	SIEF-M12B-PS-S-L-WA
SIEF-M8NB-PS-K-L	M 12	10 - 30 V DC	150	1.8	2500	Cable, 3-core	-30 / 85	4	SIEF-M8NB-PS-K-L
SIEF-M8NB-NS-K-L	M 12	10 - 30 V DC	150	1.8	2500	Cable, 3-core	-30 / 85	4	SIEF-M8NB-NS-K-L
SIEF-M12NB-PS-K-L	M 12	10 - 30 V DC	200	1.8	2500	Cable, 3-core	-30 / 85	8	SIEF-M12NB-PS-K-L
SIEF-M8NB-PS-S-L	M 12	10 - 30 V DC	150	1.8		Plug, M12x1, 3-pin	-30 / 85	4	SIEF-M8NB-PS-S-L
SIEF-M12NB-NS-S-L	M 12	10 - 30 V DC	200	1.8		Plug, M12x1, 3-pin	-30 / 85	8	SIEF-M12NB-NS-S-L
SIEF-M18B-PS-K-L	M 18	10 - 30 V DC	200		2500	Cable, 3-core	-30 / 70	5	SIEF-M18B-PS-K-L
SIEF-M18B-NS-K-L	M 18	10 - 30 V DC	200		2500	Cable, 3-core	-30 / 70	5	SIEF-M18B-NS-K-L
SIEF-M18B-PS-S-L	M 18	10 - 30 V DC	200			Plug, M12x1, 3-pin	-30 / 85	5	SIEF-M18B-PS-S-L
SIEF-M18B-PS-S-L-WA	M 18	10 - 30 V DC	200	1.8		Plug, M12x1, 3-pin	-30 / 85	5	SIEF-M18B-PS-S-L-WA
SIEF-M18B-NS-S-L	M 18	10 - 30 V DC	200			Plug, M12x1, 3-pin	-30 / 85	5	SIEF-M18B-NS-S-L
SIEF-M18NB-PS-K-L	M 18	10 - 30 V DC	200	1.8	2500	Cable, 3-core	-30 / 85	12	SIEF-M18NB-PS-K-L
SIEF-M18NB-NS-S-L	M 18	10 - 30 V DC	200	1.8		Plug, M12x1, 3-pin	-30 / 85	12	SIEF-M18NB-NS-S-L
SIEF-M30B-NS-K-L	M 30	10 - 30 V DC	200		2500	Cable, 3-core	-30 / 70	10	SIEF-M30B-NS-K-L
SIEF-M30B-PS-K-L	M 30	10 - 30 V DC	200		2500	Cable, 3-core	-30 / 70	10	SIEF-M30B-PS-K-L
SIEF-M30B-PS-S-L-WA	M 30	10 - 30 V DC	200	1.8		Plug, M12x1, 3-pin	-30 / 85	10	SIEF-M30B-PS-S-L-WA
SIEF-M30NB-NS-K-L	M 30	10 - 30 V DC	200	1.8	2500	Cable, 3-core	-30 / 85	20	SIEF-M30NB-NS-K-L
SIEF-M30NB-PS-K-L	M 30	10 - 30 V DC	200	1.8	2500	Cable, 3-core	-30 / 85	20	SIEF-M30NB-PS-K-L
SIEF-M30NB-PS-S-L-WA	M 30	10 - 30 V DC	200	1.8		Plug, M12x1, 3-pin	-30 / 85	20	SIEF-M30NB-PS-S-L-WA
SIEF-Q40S-PA-S-2L	40x40x65mm	10 - 65 V DC	200	1.8		Plug, M12x1, 4-pin	-30 / 85	35	SIEF-Q40S-PA-S-2L

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.