

FESTO Proximity sensor SIEH



Characteristics
Series: SIEH
Standard: EN 60947-5-2
Degree of protection (IP): IP69K

Manufacturer ID	Size	Voltage	Max. switching current	Max. voltage drop	Cable length	Electrical connection	Temperature range	Switching distance	Article
				V			°C	mm	
SIEH-M12B-PO-K-L	M 12	10 - 30 V DC	200	2	2500	Cable	-25 / 70	4	SIEH-M12B-PO-K-L
SIEH-M12B-PS-K-L	M 12	10 - 30 V DC	200	2	2500	Cable	-25 / 70	4	SIEH-M12B-PS-K-L
SIEH-M12B-NS-K-L	M 12	10 - 30 V DC	200	2	2500	Cable	-25 / 70	4	SIEH-M12B-NS-K-L
SIEH-M12B-NO-K-L	M 12	10 - 30 V DC	200	2	2500	Cable	-25 / 70	4	SIEH-M12B-NO-K-L
SIEH-M12B-PS-K-L-CR	M 12	10 - 30 V DC	200	2		Cable, 3-core	-25 / 70	6	SIEH-M12B-PS-K-L-CR
SIEH-M12B-NO-S-L	M 12	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	4	SIEH-M12B-NO-S-L
SIEH-M12B-PS-S-L	M 12	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	4	SIEH-M12B-PS-S-L
SIEH-M12B-PO-S-L	M 12	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	4	SIEH-M12B-PO-S-L
SIEH-M12B-NS-S-L	M 12	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	4	SIEH-M12B-NS-S-L
SIEH-M12B-PS-S-L-CR	M 12	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	6	SIEH-M12B-PS-S-L-CR
SIEH-M18B-PS-K-L	M 18	10 - 30 V DC	200	2	2500	Cable, 3-core	-25 / 70	8	SIEH-M18B-PS-K-L
SIEH-M18B-NS-K-L	M 18	10 - 30 V DC	200	2	2500	Cable, 3-core	-25 / 70	8	SIEH-M18B-NS-K-L
SIEH-M18B-PO-K-L	M 18	10 - 30 V DC	200	2	2500	Cable, 3-core	-25 / 70	8	SIEH-M18B-PO-K-L
SIEH-M18B-PS-S-L	M 18	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	8	SIEH-M18B-PS-S-L
SIEH-M18B-NS-S-L	M 18	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	8	SIEH-M18B-NS-S-L
SIEH-M18B-PO-S-L	M 18	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	8	SIEH-M18B-PO-S-L
SIEH-M18B-NO-S-L	M 18	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	8	SIEH-M18B-NO-S-L
SIEH-M18B-PS-S-L-CR	M 18	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	10	SIEH-M18B-PS-S-L-CR
SIEH-3B-PS-S-L	M 12	10 - 30 V DC	100	2	150	Cable with plug, M8x1, 3-pin	-25 / 70	1	SIEH-3B-PS-S-L
SIEH-3B-NS-S-L	M 12	10 - 30 V DC	100	2	150	Cable with plug, M8x1, 3-pin	-25 / 70	1	SIEH-3B-NS-S-L
SIEH-3B-NS-K-L	M 12	10 - 30 V DC	100	2	2500	Cable, 3-core	-25 / 70	1	SIEH-3B-NS-K-L
SIEH-3B-PS-K-L	M 12	10 - 30 V DC	100	2	2500	Cable, 3-core	-25 / 70	1	SIEH-3B-PS-K-L

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.