

FESTO Standard cylinder ESNU



Characteristics

Series: ESNU
Function: Single acting
Magnetic: Yes
Operating temperature: -20 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure bar	Article
		mm	mm	mm	in		
ESNU-8-10-P-A	Mechanical	8	10	M 5		1.5 / 10	ESNU-8-10-P-A
ESNU-8-25-P-A	Mechanical	8	25	M 5		1.5 / 10	ESNU-8-25-P-A
ESNU-10-10-P-A	Mechanical	10	10	M 5		1.5 / 10	ESNU-10-10-P-A
ESNU-10-25-P-A	Mechanical	10	25	M 5		1.5 / 10	ESNU-10-25-P-A
ESNU-10-50-P-A	Mechanical	10	50	M 5		1.5 / 10	ESNU-10-50-P-A
ESNU-12-10-P-A	Mechanical	12	10	M 5		1.5 / 10	ESNU-12-10-P-A
ESNU-12-50-P-A	Mechanical	12	50	M 5		1.5 / 10	ESNU-12-50-P-A
ESNU-16-10-P-A	Mechanical	16	10	M 5		1.2 / 10	ESNU-16-10-P-A
ESNU-16-25-P-A	Mechanical	16	25	M 5		1.2 / 10	ESNU-16-25-P-A
ESNU-16-50-P-A	Mechanical	16	50	M 5		1.2 / 10	ESNU-16-50-P-A
ESNU-20-10-P-A	Mechanical	20	10		G1/8	1.2 / 10	ESNU-20-10-P-A
ESNU-20-25-P-A	Mechanical	20	25		G1/8	1.2 / 10	ESNU-20-25-P-A
ESNU-20-50-P-A	Mechanical	20	50		G1/8	1.2 / 10	ESNU-20-50-P-A
ESNU-25-10-P-A	Mechanical	25	10		G1/8	1.2 / 10	ESNU-25-10-P-A
ESNU-25-25-P-A	Mechanical	25	25		G1/8	1.2 / 10	ESNU-25-25-P-A
ESNU-25-50-P-A	Mechanical	25	50		G1/8	1.2 / 10	ESNU-25-50-P-A
ESNU-32-25-P-A	Mechanical	32	25		G1/8	1.2 / 10	ESNU-32-25-P-A

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.