



FESTO Lubricator LOE

Characteristics

Series: LOE

Housing material: Aluminium die-cast

Seal material: NBR

Operating temperature: -10 / 60 °C

Ambient temperature: -10 / 60 °C

Reservoir capacity: 0.19 l

Size	Port thread type	Port Size	Bowl Material	Flow direction	Maximum operating pressure	Flow rate	Article
		in				l/min	
Maxi			Polycarbonate	left ? right	16		LOE-D-MAXI
Maxi	BSPP [G]	1/2	Polycarbonate	left ? right	16	8300 l/min	LOE-1/2-D-MAXI
Maxi	BSPP [G]	1	Polycarbonate	left ? right	16	9000 l/min	LOE-1-D-MAXI
Midi			Polycarbonate	left ? right	16		LOE-D-MIDI
Midi	BSPP [G]	1/4	Polycarbonate	left ? right	16	2800 l/min	LOE-1/4-D-MIDI
Midi	BSPP [G]	3/8	Polycarbonate	left ? right	16	5500 l/min	LOE-3/8-D-MIDI
Midi	BSPP [G]	1/2	Polycarbonate	left ? right	16	6100 l/min	LOE-1/2-D-MIDI
Midi	BSPP [G]	3/4	Polycarbonate	left ? right	16	6300 l/min	LOE-3/4-D-MIDI
Mini			Polycarbonate	left ? right	16		LOE-D-MINI
Mini	BSPP [G]	1/8	Polycarbonate	left ? right	16	1300 l/min	LOE-1/8-D-MINI
Mini	BSPP [G]	1/4	Polycarbonate	left ? right	16	2300 l/min	LOE-1/4-D-MINI
Mini	BSPP [G]	3/8	Polycarbonate	left ? right	16	2700 l/min	LOE-3/8-D-MINI

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.