



FESTO Lubricator MS6-LOE

Characteristics

Series: MS6-LOE

Housing material: Aluminium die-cast

Operating temperature: 0 / 60 °C

Ambient temperature: 0 / 60 °C

Reservoir capacity: 0.08 l

Size	Port thread type	Port Size	Bowl Material	Flow direction	Maximum operating pressure	Flow rate	Article
		in				l/min	
6	BSPP [G]	1/4	Polycarbonate	left ? right	16	2500 l/min	MS6-LOE-1/4-R
6	BSPP [G]	3/8	Aluminium alloy	left ? right	16	5300 l/min	MS6-LOE-3/8-U
6	BSPP [G]	3/8	Polycarbonate	left ? right	16	5300 l/min	MS6-LOE-3/8-R
6	BSPP [G]	1/2	Aluminium alloy	left ? right	16	7200 l/min	MS6-LOE-1/2-U
6	BSPP [G]	1/2	Polycarbonate	left ? right	16	7200 l/min	MS6-LOE-1/2-R-Z
6	BSPP [G]	1/2	Polycarbonate	left ? right	16	7200 l/min	MS6-LOE-1/2-R

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.