



FESTO Parallel gripper DHPS

Characteristics

Series: DHPS

Operating temperature: 5 / 60 °C

Manufacturer ID	Bore diameter mm	Operation	Stroke length mm	Connection	Total force at 6 bar, closing N	Total force at 6 bar, opening N	Operating pressure bar	Article
DHPS-6-A	6	Double acting	2	M3	25	30	2 / 8	DHPS-6-A
DHPS-10-A-NC	10	Double acting	3	M3			4 / 8	DHPS-10-A-NC
DHPS-10-A-NO	10	Double acting	3	M3			4 / 8	DHPS-10-A-NO
DHPS-10-A	10	Double acting	3	M3	70	80	2 / 8	DHPS-10-A
DHPS-16-A	16	Double acting	5	M3	190	210	2 / 8	DHPS-16-A
DHPS-16-A-NO	16	Double acting	5	M3			4 / 8	DHPS-16-A-NO
DHPS-16-A-NC	16	Double acting	5	M3			4 / 8	DHPS-16-A-NC
DHPS-20-A-NC	20	Double acting	6.5	M5			4 / 8	DHPS-20-A-NC
DHPS-20-A-NO	20	Double acting	6.5	M5			4 / 8	DHPS-20-A-NO
DHPS-20-A	20	Double acting	6.5	M5	290	320	2 / 8	DHPS-20-A
DHPS-25-A	25	Double acting	7.5	G1/8	450	500	2 / 8	DHPS-25-A
DHPS-25-A-NC	25	Double acting	7.5	G1/8			4 / 8	DHPS-25-A-NC
DHPS-25-A-NO	25	Double acting	7.5	G1/8			4 / 8	DHPS-25-A-NO
DHPS-35-A-NO	35	Double acting	12.5	G1/8			4 / 8	DHPS-35-A-NO
DHPS-35-A	35	Double acting	12.5	G1/8	910	970	2 / 8	DHPS-35-A

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.