



FESTO Parallel gripper HGPD

Characteristics

Series: HGPD

Operating temperature: 5 / 60 °C

Manufacturer ID	Bore diameter mm	Operation	Stroke length mm	Connection	Total force at 6 bar, closing N	Total force at 6 bar, opening N	Operating pressure bar	Article
HGPD-16-A-G2	16	Double acting	3	M5			4 / 8	HGPD-16-A-G2
HGPD-16-A	16	Double acting	3	M5	94	107	3 / 8	HGPD-16-A
HGPD-16-A-G1	16	Double acting	3	M5			4 / 8	HGPD-16-A-G1
HGPD-20-A	20	Double acting	4	M5	150	159	3 / 8	HGPD-20-A
HGPD-20-A-G2	20	Double acting	4	M5			4 / 8	HGPD-20-A-G2
HGPD-20-A-G1	20	Double acting	4	M5			4 / 8	HGPD-20-A-G1
HGPD-25-A-G1	25	Double acting	6	M5			4 / 8	HGPD-25-A-G1
HGPD-25-A	25	Double acting	6	M5	266	288	3 / 8	HGPD-25-A
HGPD-35-A-G2	35	Double acting	8	M5			4 / 8	HGPD-35-A-G2
HGPD-35-A-G1	35	Double acting	8	M5			4 / 8	HGPD-35-A-G1
HGPD-35-A	35	Double acting	8	M5	534	581	3 / 8	HGPD-35-A
HGPD-40-A-G1	40	Double acting	10	M5			4 / 8	HGPD-40-A-G1
HGPD-40-A	40	Double acting	10	M5	598	630	3 / 8	HGPD-40-A
HGPD-40-A-G2	40	Double acting	10	M5			4 / 8	HGPD-40-A-G2
HGPD-50-A	50	Double acting	12	G1/8	894	944	3 / 8	HGPD-50-A
HGPD-63-A	63	Double acting	16	G1/8	1.856	1.935	3 / 8	HGPD-63-A
HGPD-63-A-G2	63	Double acting	16	G1/8			4 / 8	HGPD-63-A-G2
HGPD-80-A-G1	80	Double acting	20	G1/4			4 / 8	HGPD-80-A-G1
HGPD-80-A-G2	80	Double acting	20	G1/4			4 / 8	HGPD-80-A-G2
HGPD-80-A	80	Double acting	20	G1/4	3.716	3.922	3 / 8	HGPD-80-A

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.