FESTO Parallel gripper HGPM

Characteristics

Series: HGPM
Operating temperature: 5 / 60 °C

Manufacturer ID	Bore diameter	Operation	Stroke length	Connection	Total force at 6 bar, closing	Total force at 6 bar, opening	Operating pressure	Article
	mm		mm		N	N	bar	
HGPM-08-EZ-G9	8	Single acting	2	M3	16		4 / 8	HGPM-08-EZ-G9
HGPM-08-EO-G9	8	Single acting	2	M3		16	4 / 8	HGPM-08-EO-G9
HGPM-08-EO-G6	8	Single acting	2	M3		16	4 / 8	HGPM-08-EO-G6
HGPM-08-EO-G8	8	Single acting	2	M3		16	4 / 8	HGPM-08-EO-G8
HGPM-08-EZ-G8	8	Single acting	2	M3	16		4 / 8	HGPM-08-EZ-G8
HGPM-08-EZ-G6	8	Single acting	2	M3	16		4 / 8	HGPM-08-EZ-G6
HGPM-12-EZ-G8	12	Single acting	3	M3	35		4 / 8	HGPM-12-EZ-G8
HGPM-12-EO-G8	12	Single acting	3	M3		27	4 / 8	HGPM-12-EO-G8
HGPM-12-EO-G6	12	Single acting	3	M3		27	4 / 8	HGPM-12-EO-G6
HGPM-12-EZ-G6	12	Single acting	3	M3	35		4 / 8	HGPM-12-EZ-G6
HGPM-12-EZ-G9	12	Single acting	3	M3	35		4 / 8	HGPM-12-EZ-G9
HGPM-12-EO-G9	12	Single acting	3	M3		27	4 / 8	HGPM-12-EO-G9

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR4552660373612 00_EN_29.04.2024