



FESTO Parallel gripper HGPP

Characteristics

Series: HGPP

Operating temperature: 5 / 60 °C

Manufacturer ID	Bore diameter mm	Operation	Stroke length mm	Connection	Total force at 6 bar, closing N	Total force at 6 bar, opening N	Operating pressure bar	Article
HGPP-10-A-G2	10	Double acting	2	M3			5 / 8	HGPP-10-A-G2
HGPP-10-A	10	Double acting	2	M3	80	80	2 / 8	HGPP-10-A
HGPP-10-A-G1	10	Double acting	2	M3			5 / 8	HGPP-10-A-G1
HGPP-12-A	12	Double acting	2.5	M3	116	116	2 / 8	HGPP-12-A
HGPP-16-A	16	Double acting	5	M5	204	204	2 / 8	HGPP-16-A
HGPP-20-A	20	Double acting	7.5	M5	340	340	2 / 8	HGPP-20-A
HGPP-25-A-G2	25	Double acting	10	M5			5 / 8	HGPP-25-A-G2
HGPP-25-A-G1	25	Double acting	10	M5			5 / 8	HGPP-25-A-G1
HGPP-25-A	25	Double acting	10	M5	500	500	2 / 8	HGPP-25-A
HGPP-32-A-G1	32	Double acting	12.5	G1/8			5 / 8	HGPP-32-A-G1
HGPP-32-A-G2	32	Double acting	12.5	G1/8			5 / 8	HGPP-32-A-G2
HGPP-32-A	32	Double acting	12.5	G1/8	830	830	2 / 8	HGPP-32-A

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.