



FESTO Pneumatic valve JH

Characteristics

Series: JH
Operation: Pneumatic
Operating temperature: -10 / 60 °C
Fluid: Compressed air in accordance with ISO8573-1:2010 [7:4:4]

Flow rate at 6 Bar l/min	Port Size in	Operating pressure bar	Function	Pilot supply	Construction size	Protection class	Housing material	Seal material	Article
1.1		0 / 8	5/2 Bistable	External	7	IP65	Aluminium die-cast	TPE-U(PU)	JH-5-1/4
1.1		0 / 8	5/2 Bistable	External	7	IP65	Aluminium die-cast	TPE-U(PU)	JH-5-1/4-EX
4.5	1/2	0 / 10	5/2 Bistable	External	14	IP65	Aluminium die-cast	TPE-U(PU)	JH-5-1/2
600		0 / 10	5/2 Bistable	External	5	IP65	Aluminium die-cast	TPE-U(PU)	JH-5-1/8
600		0 / 10	5/2 Bistable	External	5	IP65	Aluminium die-cast	TPE-U(PU)	JH-5-1/8-EX

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.