



FESTO Pneumatic valve VL/O

Characteristics

Series: VL/O

Operation: Pneumatic

Operating temperature: -10 / 60 °C

Fluid: Compressed air in accordance with
ISO8573-1:2010 [7:4:4]

Flow rate at 6 Bar l/min	Port thread type	Port Size in	Operating pressure bar	Function	Pilot supply	Construction size	Protection class	Housing material	Seal material	Article
3.7		1/2	-0.95 / 10	3/2 open/ closed, monostable	External	14	IP65	Aluminium die-cast	NBR	VL/O-3-1/2-EX
3.7		1/2	-0.95 / 10	3/2 open/ closed, monostable	External	14	IP65	Aluminium die-cast	NBR	VL/O-3-1/2
7.5		3/4	-0.95 / 10	3/2 open/ closed, monostable	External	19		Aluminium die-cast	NBR	VL/O-3-3/4- EX
7.5		3/4	-0.95 / 10	3/2 open/ closed, monostable	External	19		Aluminium die-cast	NBR	VL/O-3-3/4
100	PK-3		0 / 8	3/2 open, monostable		2.5		Zinc die- casting	NBR	VL/O-3-PK-3
100	PK-3		0 / 8	3/2 open, monostable		2.5		Zinc die- casting	NBR	VL/O-3-PK3X2
500			-0.95 / 10	3/2 open/ closed, monostable	External	5	IP65	Aluminium die-cast	NBR	VL/O-3-1/8-B
500			-0.95 / 10	3/2 open/ closed, monostable	External	5	IP65	Aluminium die-cast	NBR	VL/O-3-1/8-B- EX
800			-0.95 / 10	3/2 open/ closed, monostable	External	7	IP65	Aluminium die-cast	NBR	VL/O-3-1/4-EX
800			-0.95 / 10	3/2 open/ closed, monostable	External	7	IP65	Aluminium die-cast	NBR	VL/O-3-1/4

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.