

FESTO Round cylinder DSNU



- Characteristics
- Series: DSNU
- Function: Double acting
- Magnetic: Yes
- Barrel material: High alloy steel, non-corrosive
- Operating temperature: -20 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure	Article
		mm	mm	mm	in	bar	Max. 200 articles in the table
DSNU-16-10-PPV-A	Adjustable	16	10	M 5		1 / 10	DSNU-16-10-PPV-A
DSNU-16-15-PPV-A	Adjustable	16	15	M 5		1 / 10	DSNU-16-15-PPV-A
DSNU-16-20-PPV-A	Adjustable	16	20	M 5		1 / 10	DSNU-16-20-PPV-A
DSNU-16-25-PPV-A	Adjustable	16	25	M 5		1 / 10	DSNU-16-25-PPV-A
DSNU-16-30-PPV-A	Adjustable	16	30	M 5		1 / 10	DSNU-16-30-PPV-A
DSNU-16-35-PPV-A	Adjustable	16	35	M 5		1 / 10	DSNU-16-35-PPV-A
DSNU-16-40-PPV-A	Adjustable	16	40	M 5		1 / 10	DSNU-16-40-PPV-A
DSNU-16-50-PPV-A	Adjustable	16	50	M 5		1 / 10	DSNU-16-50-PPV-A
DSNU-16-60-PPV-A	Adjustable	16	60	M 5		1 / 10	DSNU-16-60-PPV-A
DSNU-16-70-PPV-A	Adjustable	16	70	M 5		1 / 10	DSNU-16-70-PPV-A
DSNU-16-80-PPV-A	Adjustable	16	80	M 5		1 / 10	DSNU-16-80-PPV-A
DSNU-16-100-PPV-A	Adjustable	16	100	M 5		1 / 10	DSNU-16-100-PPV-A
DSNU-16-125-PPV-A	Adjustable	16	125	M 5		1 / 10	DSNU-16-125-PPV-A
DSNU-16-150-PPV-A	Adjustable	16	150	M 5		1 / 10	DSNU-16-150-PPV-A
DSNU-16-160-PPV-A	Adjustable	16	160	M 5		1 / 10	DSNU-16-160-PPV-A
DSNU-16-200-PPV-A	Adjustable	16	200	M 5		1 / 10	DSNU-16-200-PPV-A
DSNU-20-10-PPV-A	Adjustable	20	10		G1/8	1 / 10	DSNU-20-10-PPV-A
DSNU-20-15-PPV-A	Adjustable	20	15		G1/8	1 / 10	DSNU-20-15-PPV-A
DSNU-20-20-PPV-A	Adjustable	20	20		G1/8	1 / 10	DSNU-20-20-PPV-A
DSNU-20-25-PPV-A	Adjustable	20	25		G1/8	1 / 10	DSNU-20-25-PPV-A
DSNU-20-30-PPV-A	Adjustable	20	30		G1/8	1 / 10	DSNU-20-30-PPV-A
DSNU-20-35-PPV-A	Adjustable	20	35		G1/8	1 / 10	DSNU-20-35-PPV-A
DSNU-20-40-PPV-A	Adjustable	20	40		G1/8	1 / 10	DSNU-20-40-PPV-A
DSNU-20-50-PPV-A	Adjustable	20	50		G1/8	1 / 10	DSNU-20-50-PPV-A
DSNU-20-60-PPV-A	Adjustable	20	60		G1/8	1 / 10	DSNU-20-60-PPV-A
DSNU-20-70-PPV-A	Adjustable	20	70		G1/8	1 / 10	DSNU-20-70-PPV-A
DSNU-20-80-PPV-A	Adjustable	20	80		G1/8	1 / 10	DSNU-20-80-PPV-A
DSNU-20-100-PPV-A	Adjustable	20	100		G1/8	1 / 10	DSNU-20-100-PPV-A
DSNU-20-125-PPV-A	Adjustable	20	125		G1/8	1 / 10	DSNU-20-125-PPV-A
DSNU-20-150-PPV-A	Adjustable	20	150		G1/8	1 / 10	DSNU-20-150-PPV-A
DSNU-20-160-PPV-A	Adjustable	20	160		G1/8	1 / 10	DSNU-20-160-PPV-A
DSNU-20-200-PPV-A	Adjustable	20	200		G1/8	1 / 10	DSNU-20-200-PPV-A
DSNU-20-250-PPV-A	Adjustable	20	250		G1/8	1 / 10	DSNU-20-250-PPV-A
DSNU-20-320-PPV-A	Adjustable	20	320		G1/8	1 / 10	DSNU-20-320-PPV-A
DSNU-25-10-PPV-A	Adjustable	25	10		G1/8	1 / 10	DSNU-25-10-PPV-A
DSNU-25-15-PPV-A	Adjustable	25	15		G1/8	1 / 10	DSNU-25-15-PPV-A
DSNU-25-20-PPV-A	Adjustable	25	20		G1/8	1 / 10	DSNU-25-20-PPV-A
DSNU-25-25-PPV-A	Adjustable	25	25		G1/8	1 / 10	DSNU-25-25-PPV-A
DSNU-25-30-PPV-A	Adjustable	25	30		G1/8	1 / 10	DSNU-25-30-PPV-A
DSNU-25-35-PPV-A	Adjustable	25	35		G1/8	1 / 10	DSNU-25-35-PPV-A

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure	Article
		mm	mm	mm	in	bar	
DSNU-25-50-PPV-A	Adjustable	25	50		G1/8	1 / 10	DSNU-25-50-PPV-A
DSNU-25-80-PPV-A	Adjustable	25	80		G1/8	1 / 10	DSNU-25-80-PPV-A
DSNU-25-100-PPV-A	Adjustable	25	100		G1/8	1 / 10	DSNU-25-100-PPV-A
DSNU-25-125-PPV-A	Adjustable	25	125		G1/8	1 / 10	DSNU-25-125-PPV-A
DSNU-25-160-PPV-A	Adjustable	25	160		G1/8	1 / 10	DSNU-25-160-PPV-A
DSNU-25-200-PPV-A	Adjustable	25	200		G1/8	1 / 10	DSNU-25-200-PPV-A
DSNU-25-250-PPV-A	Adjustable	25	250		G1/8	1 / 10	DSNU-25-250-PPV-A
DSNU-25-300-PPV-A	Adjustable	25	300		G1/8	1 / 10	DSNU-25-300-PPV-A
DSNU-25-320-PPV-A	Adjustable	25	320		G1/8	1 / 10	DSNU-25-320-PPV-A
DSNU-25-400-PPV-A	Adjustable	25	400		G1/8	1 / 10	DSNU-25-400-PPV-A
DSNU-32-40-PPV-A	Adjustable	32	40		G1/8	1 / 10	DSNU-32-40-PPV-A
DSNU-32-50-PPV-A	Adjustable	32	50		G1/8	1 / 10	DSNU-32-50-PPV-A
DSNU-32-80-PPV-A	Adjustable	32	80		G1/8	1 / 10	DSNU-32-80-PPV-A
DSNU-32-100-PPV-A	Adjustable	32	100		G1/8	1 / 10	DSNU-32-100-PPV-A
DSNU-32-125-PPV-A	Adjustable	32	125		G1/8	1 / 10	DSNU-32-125-PPV-A
DSNU-32-160-PPV-A	Adjustable	32	160		G1/8	1 / 10	DSNU-32-160-PPV-A
DSNU-32-200-PPV-A	Adjustable	32	200		G1/8	1 / 10	DSNU-32-200-PPV-A
DSNU-32-250-PPV-A	Adjustable	32	250		G1/8	1 / 10	DSNU-32-250-PPV-A
DSNU-40-25-PPV-A	Adjustable	40	25		G1/4	1 / 10	DSNU-40-25-PPV-A
DSNU-40-125-PPV-A	Adjustable	40	125		G1/4	1 / 10	DSNU-40-125-PPV-A
DSNU-10-10-P-A	Mechanical	10	10	M 5		1.5 / 10	DSNU-10-10-P-A
DSNU-10-15-P-A	Mechanical	10	15	M 5		1.5 / 10	DSNU-10-15-P-A
DSNU-10-20-P-A	Mechanical	10	20	M 5		1.5 / 10	DSNU-10-20-P-A
DSNU-10-25-P-A	Mechanical	10	25	M 5		1.5 / 10	DSNU-10-25-P-A
DSNU-10-30-P-A	Mechanical	10	30	M 5		1.5 / 10	DSNU-10-30-P-A
DSNU-10-40-P-A	Mechanical	10	40	M 5		1.5 / 10	DSNU-10-40-P-A
DSNU-10-50-P-A	Mechanical	10	50	M 5		1.5 / 10	DSNU-10-50-P-A
DSNU-10-80-P-A	Mechanical	10	80	M 5		1.5 / 10	DSNU-10-80-P-A
DSNU-10-100-P-A	Mechanical	10	100	M 5		1.5 / 10	DSNU-10-100-P-A
DSNU-12-10-P-A	Mechanical	12	10	M 5		1.5 / 10	DSNU-12-10-P-A
DSNU-12-15-P-A	Mechanical	12	15	M 5		1.5 / 10	DSNU-12-15-P-A
DSNU-12-25-P-A	Mechanical	12	25	M 5		1.5 / 10	DSNU-12-25-P-A
DSNU-12-30-P-A	Mechanical	12	30	M 5		1.5 / 10	DSNU-12-30-P-A
DSNU-12-40-P-A	Mechanical	12	40	M 5		1.5 / 10	DSNU-12-40-P-A
DSNU-12-100-P-A	Mechanical	12	100	M 5		1.5 / 10	DSNU-12-100-P-A
DSNU-12-125-P-A	Mechanical	12	125	M 5		1.5 / 10	DSNU-12-125-P-A
DSNU-12-160-P-A	Mechanical	12	160	M 5		1.5 / 10	DSNU-12-160-P-A
DSNU-12-200-P-A	Mechanical	12	200	M 5		1.5 / 10	DSNU-12-200-P-A
DSNU-16-10-P-A	Mechanical	16	10	M 5		1 / 10	DSNU-16-10-P-A
DSNU-16-15-P-A	Mechanical	16	15	M 5		1 / 10	DSNU-16-15-P-A
DSNU-16-20-P-A	Mechanical	16	20	M 5		1 / 10	DSNU-16-20-P-A
DSNU-16-25-P-A	Mechanical	16	25	M 5		1 / 10	DSNU-16-25-P-A
DSNU-16-30-P-A	Mechanical	16	30	M 5		1 / 10	DSNU-16-30-P-A
DSNU-16-35-P-A	Mechanical	16	35	M 5		1 / 10	DSNU-16-35-P-A
DSNU-16-40-P-A	Mechanical	16	40	M 5		1 / 10	DSNU-16-40-P-A
DSNU-16-50-P-A	Mechanical	16	50	M 5		1 / 10	DSNU-16-50-P-A
DSNU-16-60-P-A	Mechanical	16	60	M 5		1 / 10	DSNU-16-60-P-A
DSNU-16-70-P-A	Mechanical	16	70	M 5		1 / 10	DSNU-16-70-P-A

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure	Article
		mm	mm	mm	in	bar	
DSNU-16-80-P-A	Mechanical	16	80	M 5		1 / 10	DSNU-16-80-P-A
DSNU-16-100-P-A	Mechanical	16	100	M 5		1 / 10	DSNU-16-100-P-A
DSNU-16-125-P-A	Mechanical	16	125	M 5		1 / 10	DSNU-16-125-P-A
DSNU-16-150-P-A	Mechanical	16	150	M 5		1 / 10	DSNU-16-150-P-A
DSNU-16-160-P-A	Mechanical	16	160	M 5		1 / 10	DSNU-16-160-P-A
DSNU-16-200-P-A	Mechanical	16	200	M 5		1 / 10	DSNU-16-200-P-A
DSNU-20-10-P-A	Mechanical	20	10		G1/8	1 / 10	DSNU-20-10-P-A
DSNU-20-15-P-A	Mechanical	20	15		G1/8	1 / 10	DSNU-20-15-P-A
DSNU-20-20-P-A	Mechanical	20	20		G1/8	1 / 10	DSNU-20-20-P-A
DSNU-20-25-P-A	Mechanical	20	25		G1/8	1 / 10	DSNU-20-25-P-A
DSNU-20-30-P-A	Mechanical	20	30		G1/8	1 / 10	DSNU-20-30-P-A
DSNU-20-35-P-A	Mechanical	20	35		G1/8	1 / 10	DSNU-20-35-P-A
DSNU-20-40-P-A	Mechanical	20	40		G1/8	1 / 10	DSNU-20-40-P-A
DSNU-20-50-P-A	Mechanical	20	50		G1/8	1 / 10	DSNU-20-50-P-A
DSNU-20-60-P-A	Mechanical	20	60		G1/8	1 / 10	DSNU-20-60-P-A
DSNU-20-70-P-A	Mechanical	20	70		G1/8	1 / 10	DSNU-20-70-P-A
DSNU-20-80-P-A	Mechanical	20	80		G1/8	1 / 10	DSNU-20-80-P-A
DSNU-20-100-P-A	Mechanical	20	100		G1/8	1 / 10	DSNU-20-100-P-A
DSNU-20-125-P-A	Mechanical	20	125		G1/8	1 / 10	DSNU-20-125-P-A
DSNU-20-150-P-A	Mechanical	20	150		G1/8	1 / 10	DSNU-20-150-P-A
DSNU-20-160-P-A	Mechanical	20	160		G1/8	1 / 10	DSNU-20-160-P-A
DSNU-20-250-P-A	Mechanical	20	250		G1/8	1 / 10	DSNU-20-250-P-A
DSNU-20-300-P-A	Mechanical	20	300		G1/8	1 / 10	DSNU-20-300-P-A
DSNU-20-320-P-A	Mechanical	20	320		G1/8	1 / 10	DSNU-20-320-P-A
DSNU-25-10-P-A	Mechanical	25	10		G1/8	1 / 10	DSNU-25-10-P-A
DSNU-25-20-P-A	Mechanical	25	20		G1/8	1 / 10	DSNU-25-20-P-A
DSNU-25-25-P-A	Mechanical	25	25		G1/8	1 / 10	DSNU-25-25-P-A
DSNU-25-35-P-A	Mechanical	25	35		G1/8	1 / 10	DSNU-25-35-P-A
DSNU-25-40-P-A	Mechanical	25	40		G1/8	1 / 10	DSNU-25-40-P-A
DSNU-25-50-P-A	Mechanical	25	50		G1/8	1 / 10	DSNU-25-50-P-A
DSNU-25-60-P-A	Mechanical	25	60		G1/8	1 / 10	DSNU-25-60-P-A
DSNU-25-70-P-A	Mechanical	25	70		G1/8	1 / 10	DSNU-25-70-P-A
DSNU-25-80-P-A	Mechanical	25	80		G1/8	1 / 10	DSNU-25-80-P-A
DSNU-25-100-P-A	Mechanical	25	100		G1/8	1 / 10	DSNU-25-100-P-A
DSNU-25-125-P-A	Mechanical	25	125		G1/8	1 / 10	DSNU-25-125-P-A
DSNU-25-150-P-A	Mechanical	25	150		G1/8	1 / 10	DSNU-25-150-P-A
DSNU-25-160-P-A	Mechanical	25	160		G1/8	1 / 10	DSNU-25-160-P-A
DSNU-25-200-P-A	Mechanical	25	200		G1/8	1 / 10	DSNU-25-200-P-A
DSNU-25-250-P-A	Mechanical	25	250		G1/8	1 / 10	DSNU-25-250-P-A
DSNU-25-300-P-A	Mechanical	25	300		G1/8	1 / 10	DSNU-25-300-P-A
DSNU-25-320-P-A	Mechanical	25	320		G1/8	1 / 10	DSNU-25-320-P-A
DSNU-25-400-P-A	Mechanical	25	400		G1/8	1 / 10	DSNU-25-400-P-A
DSNU-25-500-P-A	Mechanical	25	500		G1/8	1 / 10	DSNU-25-500-P-A
DSNU-32-25-P-A	Mechanical	32	25		G1/8	1 / 10	DSNU-32-25-P-A
DSNU-32-40-P-A	Mechanical	32	40		G1/8	1 / 10	DSNU-32-40-P-A
DSNU-32-50-P-A	Mechanical	32	50		G1/8	1 / 10	DSNU-32-50-P-A
DSNU-32-80-P-A	Mechanical	32	80		G1/8	1 / 10	DSNU-32-80-P-A
DSNU-32-100-P-A	Mechanical	32	100		G1/8	1 / 10	DSNU-32-100-P-A
DSNU-32-125-P-A	Mechanical	32	125		G1/8	1 / 10	DSNU-32-125-P-A
DSNU-32-160-P-A	Mechanical	32	160		G1/8	1 / 10	DSNU-32-160-P-A
DSNU-32-200-P-A	Mechanical	32	200		G1/8	1 / 10	DSNU-32-200-P-A
DSNU-32-250-P-A	Mechanical	32	250		G1/8	1 / 10	DSNU-32-250-P-A

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure	Article
		mm	mm				
DSNU-32-320-P-A	Mechanical	32	320		G1/8	1 / 10	DSNU-32-320-P-A
DSNU-40-25-P-A	Mechanical	40	25		G1/4	1 / 10	DSNU-40-25-P-A
DSNU-40-125-P-A	Mechanical	40	125		G1/4	1 / 10	DSNU-40-125-P-A
DSNU-40-160-P-A	Mechanical	40	160		G1/4	1 / 10	DSNU-40-160-P-A
DSNU-40-200-P-A	Mechanical	40	200		G1/4	1 / 10	DSNU-40-200-P-A
DSNU-40-250-P-A	Mechanical	40	250		G1/4	1 / 10	DSNU-40-250-P-A
DSNU-16-10-PPS-A	Self-adjusting	16	10	M 5		1 / 10	DSNU-16-10-PPS-A
DSNU-16-15-PPS-A	Self-adjusting	16	15	M 5		1 / 10	DSNU-16-15-PPS-A
DSNU-16-20-PPS-A	Self-adjusting	16	20	M 5		1 / 10	DSNU-16-20-PPS-A
DSNU-16-25-PPS-A	Self-adjusting	16	25	M 5		1 / 10	DSNU-16-25-PPS-A
DSNU-16-30-PPS-A	Self-adjusting	16	30	M 5		1 / 10	DSNU-16-30-PPS-A
DSNU-16-35-PPS-A	Self-adjusting	16	35	M 5		1 / 10	DSNU-16-35-PPS-A
DSNU-16-40-PPS-A	Self-adjusting	16	40	M 5		1 / 10	DSNU-16-40-PPS-A
DSNU-16-50-PPS-A	Self-adjusting	16	50	M 5		1 / 10	DSNU-16-50-PPS-A
DSNU-16-60-PPS-A	Self-adjusting	16	60	M 5		1 / 10	DSNU-16-60-PPS-A
DSNU-16-70-PPS-A	Self-adjusting	16	70	M 5		1 / 10	DSNU-16-70-PPS-A
DSNU-16-80-PPS-A	Self-adjusting	16	80	M 5		1 / 10	DSNU-16-80-PPS-A
DSNU-16-100-PPS-A	Self-adjusting	16	100	M 5		1 / 10	DSNU-16-100-PPS-A
DSNU-16-125-PPS-A	Self-adjusting	16	125	M 5		1 / 10	DSNU-16-125-PPS-A
DSNU-16-150-PPS-A	Self-adjusting	16	150	M 5		1 / 10	DSNU-16-150-PPS-A
DSNU-16-160-PPS-A	Self-adjusting	16	160	M 5		1 / 10	DSNU-16-160-PPS-A
DSNU-16-200-PPS-A	Self-adjusting	16	200	M 5		1 / 10	DSNU-16-200-PPS-A
DSNU-20-10-PPS-A	Self-adjusting	20	10		G1/8	1 / 10	DSNU-20-10-PPS-A
DSNU-20-15-PPS-A	Self-adjusting	20	15		G1/8	1 / 10	DSNU-20-15-PPS-A
DSNU-20-20-PPS-A	Self-adjusting	20	20		G1/8	1 / 10	DSNU-20-20-PPS-A
DSNU-20-25-PPS-A	Self-adjusting	20	25		G1/8	1 / 10	DSNU-20-25-PPS-A
DSNU-20-35-PPS-A	Self-adjusting	20	35		G1/8	1 / 10	DSNU-20-35-PPS-A
DSNU-20-40-PPS-A	Self-adjusting	20	40		G1/8	1 / 10	DSNU-20-40-PPS-A
DSNU-20-50-PPS-A	Self-adjusting	20	50		G1/8	1 / 10	DSNU-20-50-PPS-A
DSNU-20-60-PPS-A	Self-adjusting	20	60		G1/8	1 / 10	DSNU-20-60-PPS-A
DSNU-20-70-PPS-A	Self-adjusting	20	70		G1/8	1 / 10	DSNU-20-70-PPS-A
DSNU-20-80-PPS-A	Self-adjusting	20	80		G1/8	1 / 10	DSNU-20-80-PPS-A
DSNU-20-100-PPS-A	Self-adjusting	20	100		G1/8	1 / 10	DSNU-20-100-PPS-A
DSNU-20-125-PPS-A	Self-adjusting	20	125		G1/8	1 / 10	DSNU-20-125-PPS-A
DSNU-20-150-PPS-A	Self-adjusting	20	150		G1/8	1 / 10	DSNU-20-150-PPS-A
DSNU-20-160-PPS-A	Self-adjusting	20	160		G1/8	1 / 10	DSNU-20-160-PPS-A
DSNU-20-200-PPS-A	Self-adjusting	20	200		G1/8	1 / 10	DSNU-20-200-PPS-A
DSNU-20-250-PPS-A	Self-adjusting	20	250		G1/8	1 / 10	DSNU-20-250-PPS-A
DSNU-20-300-PPS-A	Self-adjusting	20	300		G1/8	1 / 10	DSNU-20-300-PPS-A
DSNU-20-320-PPS-A	Self-adjusting	20	320		G1/8	1 / 10	DSNU-20-320-PPS-A
DSNU-25-10-PPS-A	Self-adjusting	25	10		G1/8	1 / 10	DSNU-25-10-PPS-A
DSNU-25-15-PPS-A	Self-adjusting	25	15		G1/8	1 / 10	DSNU-25-15-PPS-A
DSNU-25-20-PPS-A	Self-adjusting	25	20		G1/8	1 / 10	DSNU-25-20-PPS-A
DSNU-25-35-PPS-A	Self-adjusting	25	35		G1/8	1 / 10	DSNU-25-35-PPS-A
DSNU-25-40-PPS-A	Self-adjusting	25	40		G1/8	1 / 10	DSNU-25-40-PPS-A
DSNU-25-50-PPS-A	Self-adjusting	25	50		G1/8	1 / 10	DSNU-25-50-PPS-A
DSNU-25-80-PPS-A	Self-adjusting	25	80		G1/8	1 / 10	DSNU-25-80-PPS-A
DSNU-25-125-PPS-A	Self-adjusting	25	125		G1/8	1 / 10	DSNU-25-125-PPS-A
DSNU-25-320-PPS-A	Self-adjusting	25	320		G1/8	1 / 10	DSNU-25-320-PPS-A

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure	Article
		mm	mm	mm	in	bar	
DSNU-25-400-PPS-A	Self-adjusting	25	400		G1/8	1 / 10	DSNU-25-400-PPS-A
DSNU-32-40-PPS-A	Self-adjusting	32	40		G1/8	1 / 10	DSNU-32-40-PPS-A
DSNU-32-50-PPS-A	Self-adjusting	32	50		G1/8	1 / 10	DSNU-32-50-PPS-A
DSNU-32-80-PPS-A	Self-adjusting	32	80		G1/8	1 / 10	DSNU-32-80-PPS-A
DSNU-32-200-PPS-A	Self-adjusting	32	200		G1/8	1 / 10	DSNU-32-200-PPS-A
DSNU-32-250-PPS-A	Self-adjusting	32	250		G1/8	1 / 10	DSNU-32-250-PPS-A
DSNU-40-25-PPS-A	Self-adjusting	40	25		G1/4	1 / 10	DSNU-40-25-PPS-A
DSNU-40-100-PPS-A	Self-adjusting	40	100		G1/4	1 / 10	DSNU-40-100-PPS-A
DSNU-40-125-PPS-A	Self-adjusting	40	125		G1/4	1 / 10	DSNU-40-125-PPS-A
DSNU-40-160-PPS-A	Self-adjusting	40	160		G1/4	1 / 10	DSNU-40-160-PPS-A

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.