



FESTO Angle seat valve VZXF

Characteristics

Series: VZXF
Operation: Pneumatic
Operating temperature: -40 / 200 °C
Fluid: Compressed air in accordance with ISO8573-1:2010 [7:4:4]

Port thread type	Port Size in	Operating pressure bar	Function	Construction size	Article
BSPP (G)	1/8	6 / 10	2/2 closed, monostable	13	1002513-FESTO
BSPP (G)	1/8	6 / 10	2/2 closed, monostable	24	1002517-FESTO
BSPP (G)	1/8	6 / 10	2/2 closed, monostable	35	3536850-FESTO
BSPP (G)	1/8	6 / 10	2/2 closed, monostable	35	3535824-FESTO
BSPP (G)	1/8	6 / 10	2/2 closed, monostable	35	3535720-FESTO
BSPP (G)	1/8	6 / 10	2/2 closed, monostable	12	3535619-FESTO
BSPP (G)	1/8	6 / 10	2/2 closed, monostable	23	3535664-FESTO
BSPP (G)	1/8	6 / 10	2/2 closed, monostable	43	3540796-FESTO
BSPP (G)	1/8	6 / 10	2/2 closed, monostable	35	3539368-FESTO
BSPP (G)	1/8	6 / 10	2/2 closed, monostable	12	3539036-FESTO
BSPP (G)	1/8	6 / 10	2/2 closed, monostable	12	3535620-FESTO
BSPP (G)	1/8	6 / 10	2/2 closed, monostable	23	3539248-FESTO
BSPP (G)	1/8	6 / 10	2/2 closed, monostable	43	3536436-FESTO
BSPP (G)	1/8	6 / 10	2/2 closed, monostable	16	3539179-FESTO
BSPP (G)	1/8	6 / 10	2/2 closed, monostable	16	3535644-FESTO

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.