

FESTO Spiral plastic tubing PUN-S



Characteristics

Series: PUN-S

Hose material: TPE-U(PU)

With couplers: No

Temperature range: -35 / 60 °C

Outer diameter	Internal diameter	Colour	Maximum working length	Maximum operating pressure at 20 °C	Article
mm	mm		m	bar	
4	2.6	Black	0.5	10	PUN-4X0.75-S-0.5-SW
4	2.6	Black	1.5	10	PUN-4X0.75-S-1.5-SW
4	2.6	Black	1.5	10	PUN-4X0.75-S-1-SW
4	2.6	Blue	0.5	10	PUN-4X0.75-S-0.5-BL
4	2.6	Blue	1.5	10	PUN-4X0.75-S-1-BL
6	4	Black	1.5	10	PUN-6X1-S-1-SW
6	4	Black	2	10	PUN-6X1-S-2-SW
6	4	Black	6	10	PUN-6X1-S-6-SW
6	4	Blue	2	10	PUN-6X1-S-2-BL
6	4	Blue	6	10	PUN-6X1-S-6-BL
8	5.7	Black	1.5	10	PUN-8X1.25-S-1-SW
8	5.7	Black	2	10	PUN-8X1.25-S-2-SW
8	5.7	Black	6	10	PUN-8X1.25-S-6-SW
8	5.7	Blue	1.5	10	PUN-8X1.25-S-1-BL
8	5.7	Blue	2	10	PUN-8X1.25-S-2-BLUE
8	5.7	Blue	6	10	PUN-8X1.25-S-6-BL
10	7	Black	2	10	PUN-10X1.5-S-2-SW
10	7	Black	6	10	PUN-10X1.5-S-6-SW
10	7	Blue	1.5	10	PUN-10X1.5-S-1-BL
10	7	Blue	2	10	PUN-10X1.5-S-2-BL
10	7	Blue	6	10	PUN-10X1.5-S-6-BL
12	8	Black	1.5	10	PUN-12X2-S-1-SW
12	8	Black	6	10	PUN-12X2-S-6-SW
12	8	Blue	1.5	10	PUN-12X2-S-1-BL
12	8	Blue	2	10	PUN-12X2-S-2-BL
12	8	Blue	6	10	PUN-12X2-S-6-BL

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.