


FESTO Toothed belt axis EGC



Characteristics

Series: EGC

Operating temperature: -10 / 60 °C

Degree of protection (IP): 40

Construction size	Stroke length	Repetition accuracy	Max. feed force Fx	Article
	mm	mm	N	
70	300	±0.08	100	3012492-FESTO
70	400	±0.08	100	3012493-FESTO
70	500	±0.08	100	3012494-FESTO
70	600	±0.08	100	3012495-FESTO
70	800	±0.08	100	3012496-FESTO
70	1000	±0.08	100	3012497-FESTO
70	1200	±0.08	100	3012498-FESTO
80	400	±0.08	350	575832-FESTO
80	500	±0.08	350	3013354-FESTO
80	600	±0.08	350	3013355-FESTO
80	800	±0.08	350	3013356-FESTO
80	1000	±0.08	350	3013357-FESTO
80	1200	±0.08	350	3013359-FESTO
120	500	±0.08	800	3013365-FESTO
120	800	±0.08	800	3013367-FESTO
120	1500	±0.08	800	3013370-FESTO

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.