

FESTO Non-Return valve H



Characteristics

Series: H

Mounting: Threaded

Operating pressure: -1 / 10 bar

Operating temperature: -10 / 60 °C

Seal material: NBR

Fluid: Compressed air in accordance with
ISO8573-1:2010 [7:4:4]

Fitting type	Design form	Material	Tube Outside Diameter	Thread type	Thread size	Flow Rate (6 bar - delta p = 1 bar) NI/min	Article
Check valve	Compact	Anodised aluminium	4			136	H-QS-4
Check valve	Compact	Anodised aluminium	6			282	H-QS-6
Check valve	Compact	Anodised aluminium	8			681	H-QS-8
Check valve	Compact	Anodised aluminium	10			1480	H-QS-10
Check valve	Compact	Anodised aluminium	12			1715	H-QS-12
Check valve	Compact	Brass		Inner thread/outer thread	1/8	280	H-1/8-A/I
Check valve	Compact	Wrought aluminium alloy, anodized		External thread BSPP (G)	1/2	5500	H-1/2-B
Check valve	Compact	Wrought aluminium alloy, anodized		External thread BSPP (G)	1/4	1000	H-1/4-B
Check valve	Compact	Wrought aluminium alloy, anodized		External thread BSPP (G)	3/4	5900	H-3/4-B
Check valve	Compact	Wrought aluminium alloy, anodized		External thread BSPP (G)	3/8	2000	H-3/8-B

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.