



FESTO Non-Return valve HA

Characteristics

Series: HA

Mounting: Threaded

Operating pressure: -1 / 10 bar

Operating temperature: 0 / 60 °C

Fluid: Compressed air in accordance with
ISO8573-1:2010 [7:-:-]

Fitting type	Design form	Material	Tube Outside Diameter	Thread type	Thread size	Flow Rate (6 bar - delta p = 1 bar) NI/min	Article
Check valve	Compact	Anodised aluminium	10	External thread BSPT (R)	3/8	1740	HA-3/8-QS-10
Check valve	Compact	Anodised aluminium	12	External thread BSPT (R)	1/2	2230	HA-1/2-QS-12
Check valve	Compact	Anodised aluminium	12	External thread BSPT (R)	3/8	1876	HA-3/8-QS-12
Check valve	Compact	Brass, Nickel-plated	4	External thread BSPT (R)	1/8	138	HA-1/8-QS-4
Check valve	Compact	Brass, Nickel-plated	4	Outer thread metric	M5	148	HA-M5-QS-4
Check valve	Compact	Brass, Nickel-plated	6	External thread BSPT (R)	1/4	302	HA-1/4-QS-6
Check valve	Compact	Brass, Nickel-plated	6	External thread BSPT (R)	1/8	311	HA-1/8-QS-6
Check valve	Compact	Brass, Nickel-plated	8	External thread BSPT (R)	1/4	670	HA-1/4-QS-8
Check valve	Compact	Brass, Nickel-plated	8	External thread BSPT (R)	1/8	331	HA-1/8-QS-8

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.