



FESTO Non-Return valve HB

Characteristics

Series: HB

Mounting: Threaded

Operating pressure: -1 / 10 bar

Operating temperature: 0 / 60 °C

Fluid: Compressed air in accordance with
ISO8573-1:2010 [7:-:-]

Fitting type	Design form	Material	Tube Outside Diameter	Thread type	Thread size	Flow Rate (6 bar - delta p = 1 bar) NI/min	Article
Check valve	Compact	Anodised aluminium	10	External thread BSPT (R)	3/8	1700	HB-3/8-QS-10
Check valve	Compact	Anodised aluminium	12	External thread BSPT (R)	1/2	2206	HB-1/2-QS-12
Check valve	Compact	Anodised aluminium	12	External thread BSPT (R)	3/8	1886	HB-3/8-QS-12
Check valve	Compact	Brass, Nickel-plated	4	External thread BSPT (R)	1/8	142	HB-1/8-QS-4
Check valve	Compact	Brass, Nickel-plated	4	Outer thread metric	M5	144	HB-M5-QS-4
Check valve	Compact	Brass, Nickel-plated	6	External thread BSPT (R)	1/4	294	HB-1/4-QS-6
Check valve	Compact	Brass, Nickel-plated	6	External thread BSPT (R)	1/8	335	HB-1/8-QS-6
Check valve	Compact	Brass, Nickel-plated	8	External thread BSPT (R)	1/4	696	HB-1/4-QS-8
Check valve	Compact	Brass, Nickel-plated	8	External thread BSPT (R)	1/8	314	HB-1/8-QS-8

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.