

FESTO Barbed T-Fitting TCN

Characteristics

Series: TCN

Operating temperature: $0 / 60 \,^{\circ}\text{C}$ Operating pressure: -0.95 / 10 bar

Manufacturer ID	Material	Connection 1	Connection 2	Nominal size mm	Wrench width mm	Article
TCN-1/8-PK-3	Aluminium, Die-cast steel	Tubing O.D. 4mm	1/8" BSPP(G)	13	13	TCN-1/8-PK-3
TCN-1/4-PK-4	Aluminium, Die-cast steel	Tubing O.D. 6mm	1/4" BSPP(G)	17	17	TCN-1/4-PK-4
TCN-1/8-PK-4	Aluminium, Die-cast steel	Tubing O.D. 6mm	1/8" BSPP(G)	13	13	TCN-1/8-PK-4
TCN-1/4-PK-6	Aluminium, Die-cast steel	Tubing O.D. 8mm	1/4" BSPP(G)	17	17	TCN-1/4-PK-6
TCN-1/8-PK-6	Aluminium, Die-cast steel	Tubing O.D. 8mm	1/8" BSPP[G]	13	13	TCN-1/8-PK-6
TCN-3/8-PK-6	Aluminium, Die-cast steel	Tubing O.D. 8mm	3/8" BSPP(G)	19	19	TCN-3/8-PK-6
TCN-M3-PK-2	High alloy steel, Zinc die-cast	Tubing O.D. 3mm	M3	4.5	4.5	TCN-M3-PK-2
TCN-M3-PK-3	High alloy steel, Zinc die-cast	Tubing O.D. 4mm	M3	4.5	4.5	TCN-M3-PK-3
TCN-M5-PK-2	Steel, Zinc die-cast	Tubing O.D. 3mm	M5	4.5	4.5	TCN-M5-PK-2

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

ERIKS

PR455266037361526_EN_05.05.2024